

OMNITRONIC PAS-212 MK3 2-Way Top

Passive speaker with 12" woofer, 1" driver and 300 W RMS





The article is no longer in our assortment.

Features:

- 2-way bass-reflex system with 30 cm woofer (8 cm voice coil)
- 2.5 cm compression driver with ferrite magnet (3.8 cm voice coil with polymer diaphragm)
- Optimized for combination with PAS subwoofers
- With rigging points
- Dual flange
- Black metal grille with acoustic foam
- 2 recessed carrying handles
- Application possibility: Standing; suspended; monitoring; on stand
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; rental
- Package contents
- 1 x user manual, 1 x compact cabinet speaker

Technical specifications:

Power:	Program: 600W Rated: 300W RMS
Frequency range:	60 - 20000 Hz
Sensitivity:	98 dB (1W/1m)
Max. SPL:	126 dB
Dispersion angle:	90° x 60°
Impedance:	8 ohms

Logistic

EAN / GTIN: 4026397660913 Weight: 21,95 kg Length: 0.44 m Width: 0.43 m Heigth: 0.68 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Attachment system:	Dual flange: Ø 35mm (0°/5°)
Flying points:	4 x M10 thread; 6 x M8 thread
Connections:	Input: speaker via 2 x speaker built-in socket (F)
Crossover frequency:	3000 Hz
Speaker:	1 x woofer 12" with ferrit magnet
	Basket material: aluminum
	Voice coil lows 3"
	1 x compression tweeter highs 1"
	Voice coil compression tweeter highs 1,5"
	Horn vent 1"
Type of speaker:	Compact cabinet speaker
Recessed carrying handle:	2 pc/pcs
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 39 cm
	Depth: 61,5 cm
	Height: 38 cm
Weight:	20,60 kg