

OMNITRONIC PAS-151A PRO DSP Active Subwoofer

Active 15" PA bassreflex subwoofer, 500 W RMS

Art. No.: 11039630

GTIN: 4026397527452



The article is no longer in our assortment.

Features:

- Active high-power bassreflex subwoofer for permanent installations and touring purposes
- Housing made of 18 mm plywood multilayered glued
- 1000 W Class D power amplifier with switch mode power supply
- 38 cm (15") bass speaker
- Balanced signal input XLR/6.3 mm jack L/R
- Parallel XLR line output L/R
- Adjustable crossover frequency 80-200 Hz
- DSP-controlled limiter
- Phase reversal switch
- M20 metal flange for mounting top speakers
- Incorporated carrying handles
- Scratch-resistant lacquer surface, steel grille and rubber feet
- Matching castors optionally available
- Digital signal processor
- Wheels optional

Logistic

EAN / GTIN: 4026397527452

Weight: 47,25 kg

Length: 0.78 m

Width: 0.56 m

Height: 0.70 m

Bulky product

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 670 W |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |

| | |
|----------------------|---|
| Power: | Rated: 500W RMS Program: 1000W |
| Frequency range: | 45 - 120 Hz |
| Sensitivity: | 96 dB |
| Max. SPL: | 126 dB |
| DSP: | Digital signal processor |
| Circuitry: | Class D |
| Crossover frequency: | 80-200 Hz |
| Speaker: | 1 x woofer 15" |
| Type of speaker: | Subwoofer |
| Transport aid: | Wheels optional |
| Dimensions: | Width: 46 cm Depth: 68 cm Height: 59 cm |
| Weight: | 42,60 kg |
| Woofer: | 38 cm (15") |
| Signal input: | XLR L/R |
| Signal output: | XLR L/R |
| Acoustic loading: | Bassreflex |
| Amplifier: | Class D |