

OMNITRONIC PAS-181A PRO DSP Active Subwoofer

Active 18" PA bassreflex subwoofer, 1200 W

Art. No.: 11039631

GTIN: 4026397527469



The article is no longer in our assortment.

Features:

- Active high-power bassreflex subwoofer for permanent installations and touring purposes
- Housing made of 18 mm plywood multilayered glued
- 1200 W Class D power amplifier with switch mode power supply
- 45 cm (18") bass speaker
- Balanced XLR input L/R
- Parallel XLR line output L/R
- Adjustable crossover frequency 80-200 Hz
- DSP-controlled limiter
- Phase reversal switch
- M20 metal flange for mounting top speakers
- Incorporated carrying handles
- Scratch-resistant lacquer surface, steel grille and rubber feet
- Matching castors optionally available
- Digital signal processor
- Wheels optional

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	670 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)



EAN / GTIN: 4026397527469 Weight: 61,40 kg Length: 0.91 m Width: 0.66 m Heigth: 0.80 m Bulky product











Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power:	Program: 1200W Rated: 600W RMS
Frequency range:	40 - 120 Hz
Sensitivity:	96 dB
Max. SPL:	126 dB
DSP:	Digital signal processor
Attachment system:	Ø 35mm
Circuitry:	Class D
Connections:	Input: line via 2 x 3-pin XLR Output: line via 2 x 3-pin XLR
Crossover frequency:	80-200 Hz
Speaker:	1 x woofer 18"
Type of speaker:	Subwoofer
Type of construction:	Vented
Transport aid:	Wheels optional
Dimensions:	Width: 56 cm
	Depth: 80 cm
	Height: 69 cm
Weight:	54,70 kg