

PSSO CSA-228B top, black

Compact speaker array for touring purposes and permanent installations

Art. No.: 11040800 GTIN: 4026397362701



The article is no longer in our assortment.

Description:

The CSA high-mid speaker units,

they are very powerful and feature a horn tweeter with 3.5 cm driver and, depending on the model, one or two 20 cm woofers (CSA-218 or CSA-228 respectively). The tweeter of the smaller version, the CSA-218, ensures a horizontal and vertical dispersion angle of 90°. Thus the CSA-218 can be used standing or lying without having to make compromises in terms of sound or directivity. The larger version, the CSA-228, is designed for upright use and has a dispersion angle of 90° x 40°.

Where should the CSA be used?

We can recommend mobile use. Concerts or weddings are supported in a powerful, resonant and linear way. But as it is quite versatile, the CSA should not be reduced to our suggestion only.

Features:

- Compact speaker array for touring purposes and permanent installations
- Speaker flange for mobile use included in the delivery
- Mounting bracket for permanent installation can be ordered separately
- Lightweight housing due to high-quality plastic
- Wide horizontal dispersion angle

Technical specifications:

Frequency range:

75 - 18000 Hz

Logistic

EAN / GTIN: 4026397362701 Weight: 17,10 kg Length: 0.76 m Width: 0.42 m Heigth: 0.40 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Dimensions:	Width: 66,5 cm
	Depth: 34 cm
	Height: 25 cm
Weight:	14,45 kg
Rated power:	300 W RMS
Program power:	600 W
Components:	2 x 20 cm mids speaker (2 x 8"), 3.4 cm driver (1.33")
Connection:	2 Speaker sockets (4-pin)
Sensitivity:	95 dB
Maximum SPL:	119 dB
Impedance:	8 ohms
Crossover frequency:	2.5 kHz
Dispersion angle:	H=90°, V=40°
Dimensions (H x W x D):	250 x 665 x 340 mm