

PSSO CSA-115CXA Active Subwoofer black

Active 15" PA bassreflex subwoofer, 1000 W

Art. No.: 11040819

GTIN: 4026397527667



Features:

- Active high-power bassreflex subwoofer for permanent installations and touring purposes
- High-performance Class D power amplifier (1000 W) with switch mode power supply
- 38 cm (15") bass speaker
- Balanced XLR input
- XLR line output with high-pass filter (100 Hz) for the active top speakers CSA-218A and CSA-228A
- PowerCon mains input with parallel output for power supply of one top speaker (CSA-218A/CSA-228A)
- Limiter and protection set against short-circuit, overheat and overload
- MDF housing (18 mm) with scratch-resistant lacquer surface, steel grille and flange
- Carrying handles and rubber feet
- Stackable

Logistic

EAN / GTIN: 4026397527667

Weight: 43,35 kg

Length: 0.73 m

Width: 0.53 m

Height: 0.75 m

Bulky product

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power:	1000W
Frequency range:	35 - 95 Hz
Speaker:	15"
Rated power:	1000 W
Components:	LF: 38 cm (15")
Crossover frequency:	HPF: 30 Hz, LPF: 100 Hz

Dispersion angle:	-
Maximum SPL:	123 dB
Acoustic loading:	Bassreflex
Cabinet material:	MDF (18 mm)
Amplifier:	Class D
THD:	<0.1 %
S/N ratio:	>80 dB
Damping factor:	>50
Input sensitivity:	2 V
Input impedance:	40 kohms/20 kohms (bal./unbal.)
Signal input:	XLR
Signal output:	XLR (HPF 100 Hz)
Power consumption:	1000 W
Protection circuits:	Limiter, overheat, overload, short-circuit
LED indicators:	Power, signal, clip
Weight:	37 kg

Scope of delivery:
