

PSSO K-215 2-Way Top 400W

PRO PA speaker, 15" woofer, 1" horn, 400 W RMS, 8 ohms

Art. No.: 11041108

GTIN: 4026397481846



The article is no longer in our assortment.

Features:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable 25 mm constant directivity horn tweeter (1", 44 mm voice coil)
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- European engineering

Logistic

EAN / GTIN: 4026397481846

Weight: 28,60 kg

Length: 0.48 m

Width: 0.51 m

Height: 0.80 m

Technical specifications:

Power:	Program: 800W
	Rated: 400W RMS
Frequency range:	47 - 19000 Hz
Sensitivity:	98 dB
Max. SPL:	130 dB

Dispersion angle:	80° x 50°
Impedance:	8 ohms
Connections:	Input: speaker via 2 x 2-pin SpeakON mounting version (F)
Crossover frequency:	1700 Hz
Speaker:	1 x woofer 15" 1 x horn 1"
Type of speaker:	Compact cabinet speaker
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Dimensions:	Width: 44,5 cm Depth: 41,5 cm Height: 71 cm
Weight:	25,65 kg