

PSSO K-215 2-Way Top 400W

PRO PA speaker, 15" woofer, 1" horn, 400 W RMS, 8 ohms

Art. No.: 11041108 GTIN: 4026397481846



The article is no longer in our assortment.

Features:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable 25 mm constant directivity horn tweeter (1", 44 mm voice coil)
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- European engineering

Technical specifications:

| Power: | Program: 800W | |
|------------------|-----------------|--|
| | Rated: 400W RMS | |
| Frequency range: | 47 - 19000 Hz | |
| Sensitivity: | 98 dB | |
| Max. SPL: | 130 dB | |

Logistic

EAN / GTIN: 4026397481846

Weight: 28,60 kg Length: 0.48 m Width: 0.51 m Heigth: 0.80 m

| Dispersion angle: | 80° x 50° |
|----------------------|---|
| Impedance: | 8 ohms |
| Connections: | Input: speaker via 2 x 2-pin SpeakON mounting version (F) |
| Crossover frequency: | 1700 Hz |
| Speaker: | 1 x woofer 15" 1 x horn 1" |
| Type of speaker: | Compact cabinet speaker |
| Use of brands: | CELTO ACOUSTIQUE driver Built with NEUTRIK connector |
| Dimensions: | Width: 44,5 cm Depth: 41,5 cm Height: 71 cm |
| Weight: | 25,65 kg |