

PSSO K-215X 2-way top 600W

Pro PA speaker system

Art. No.: 11041110

GTIN: 4026397483048

**The article is no longer in our assortment.****Features:**

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable constant directivity horn tweeter
- Horn exit 35 mm (1.4")
- Voice coil 72 mm (2.8")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended

Technical specifications:

Rated power:	600 W RMS
Components:	38 cm woofer (15"), 3.6 cm horn (1.4")
Connection:	2 x Speakon
Sensitivity:	98 dB
Maximum SPL:	132 dB

Logistic

EAN / GTIN: 4026397483048

Weight: 35,00 kg

Length: 0.52 m

Width: 0.48 m

Height: 0.79 m

Volume: 0.05 m³

Bulky product

Accessories:Art. No.: 30001169
Eye Bolt M10/50mm, Stainless SteelArt. No.: 60004617
WH-2 Wall-Mounting 40 kg max

Crossover frequency:	1.5 kHz
Dispersion angle:	80° x 50°
Dimensions (H x W x D):	710 x 445 x 415 mm
Weight:	32 kg
Size of woofer:	38 cm (15")
Number of bass-woofer:	1 Stück
Frequency range:	44 - 19000 Hz
Height:	41,5 cm
Depths:	44,5 cm
Width:	71 cm
Loudspeaker control:	8 Ohm