

## **PSSO PRIME-12CX Coaxial Speaker, 400W**

GTIN: 4026397494013



## The article is no longer in our assortment.

## Features:

- Rugged full-range PA top speaker, qualified for suspension and clubs
- Housing made of 18 mm (13 layers) birch plywood
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 30 cm neodymium bass speaker (12") with diecast aluminum basket
- 36 mm neodymium driver (1.4"), 72 mm voice coil (2.8")
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Movable mounting bracket for ceiling or wall installation
- Scratch-resistant lacquer surface
- Applications: standing, on a subwoofer or suspended
- CELTO ACOUSTIQUE driver
- European engineering

## **Technical specifications:**

Power:	Program: 800W Rated: 400W RMS
Frequency range:	59 - 21000 Hz
Sensitivity:	100 dB
Max. SPL:	132 dB
Dispersion angle:	70° x 70°



EAN / GTIN: 4026397494013 Weight: 17,00 kg Length: 0.48 m Width: 0.48 m Heigth: 0.49 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Impedance:	8 ohms
Connections:	Input: speaker via 2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	1400 Hz
Speaker:	1 x woofer 12"
	1 x horn 1,5"
	Voice coil lows 3"
	Horn vent 1,35"
	Voice coil compression tweeter highs 3"
Type of speaker:	Coaxial speaker; compact cabinet speaker
Use of brands:	CELTO ACOUSTIQUE driver
Dimensions:	Width: 38 cm
	Depth: 38 cm
	Height: 38 cm
Weight:	14,80 kg