


PSSO KX-P212A 2-way Speaker, active, DSP

Active speaker with 12" woofer, 1" driver, 700 W RMS,

Art. No.: 11041180

GTIN: 4026397743920



List price: 593.81 €

incl. 19% VAT.

Features:

- Active 12/2 full range system for mobile live and DJ applications
- Versatile setup options with the KX subwoofer and specially tuned presets
- High-quality and sturdy PP cabinet with internal bracing, qualified for suspension
- DSP-controlled biamp amplifier (class D)
- 2-way bass-reflex system
- Line input (XLR/6.3 mm jack) with separate level control
- Mic/line input (XLR/6.3 mm jack) with separate level control
- Mixed output for linking further active speaker systems
- Digital signal processor FIR Filter
- DSP presets: LIVE; MONITOR; MUSIC; SPEECH; SUB; FLAT
- The device is cooled by passive convection cooling
- With rigging points
- Black metal grille with acoustic foam
- 3 Rugged carrying handles

Package contents

- 1 x top, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397743920

Weight: 19,83 kg

Length: 0.41 m

Width: 0.41 m

Height: 0.69 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 1000 W

IP classification: IP20

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Power:	700W RMS Peak: 1400W
Frequency range:	56 - 20000 Hz
Max. SPL:	135 dB
DSP:	Digital signal processor FIR Filter
DSP presets:	LIVE; MONITOR; MUSIC; SPEECH; SUB; FLAT
Dispersion angle:	90° x 60°
Cooling:	Passive convection cooling
Attachment system:	Flange:
Flying points:	3 x M10 thread
Circuitry:	Class D Biamp
Control elements:	Power switch, groundlift selector, Input sensitivity switch, DSP preset switch, level control per channel
Controls:	Overheat; DC voltage; short-circuit; limiter
Status LED:	Power, signal, clip
Connections:	Input: mic/line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Output: line via 1 x 3-pin XLR (M) mounting version
Speaker:	1 x woofer 12" with ferrit magnet Basket material: steel Conematerial: cardboard/paper Voice coil lows 3" 1 x compression tweeter highs 1" with ferrit magnet Voice coil compression tweeter highs 1,5"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Carrying handle:	3 pc/pcs
Material:	PP polypropylene, powder-coated
Color:	Black, matte
Dimensions:	Width: 35 cm Depth: 33,5 cm Height: 63 cm
Weight:	17,75 kg
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	2,5 m detachable