

## PSSO KX-181A Subwoofer, active, DSP

Active 18" PA bassreflex subwoofer, 1400 W RMS

Art. No.: 11041182

GTIN: 4026397745375



### Features:

- Active PA subwoofer for touring applications and permanent installations
- Versatile setup options with the KX top speakers and specially tuned presets
- Endfire and cardioid array configurations possible
- Digital signal processor
- DSP presets: 80 Hz hi cut; 90 Hz hi cut; 100 Hz hi cut; 120 Hz hi cut; End Fire 80 Hz; Inverted/Cardioid 80 Hz
- The device is cooled by temperature-controlled fan
- Black metal grille with acoustic foam
- 4 Rugged carrying handles
- Mains input and output for power linking up to 4 units

### Logistic

EAN / GTIN: 4026397745375

Weight: 57,65 kg

Length: 0.83 m

Width: 0.64 m

Height: 0.70 m

Bulky product

### Technical specifications:

|                    |   |
|--------------------|---|
| Power supply:      | 230 V AC, 50 Hz   |
| Power consumption: | 1800 W  |
| IP classification: | IP20  |
| Protection class:  | Protection class I  |
| Power connection:  | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided) |
| Power output:      | 1 x P-Con (gray), mounting version  |
| Device fuse:       | 5 x 20 mm, F 8 A fuse replaceable   |

|                       |  |
|-----------------------|--|
| Power:                | 1400W RMS<br>Peak: 2800W   |
| Frequency range:      | 30 - 400 Hz  |
| Max. SPL:             | 134 dB   |
| DSP:                  | Digital signal processor   |
| DSP presets:          | 80 Hz hi cut; 90 Hz hi cut; 100 Hz hi cut; 120 Hz hi cut; End Fire 80 Hz; Inverted/Cardioid 80 Hz  |
| Cooling:              | 1 x temperature-controlled fan   |
| Attachment system:    | M20 thread   |
| Circuitry:            | Class D  |
| Control elements:     | Power switch, groundlift selector, level control, DSP preset switch  |
| Controls:             | Overheat; short-circuit; DC voltage; limiter   |
| Status LED:           | Power, signal, clip  |
| Connections:          | Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Output: line via 2 x 3-pin XLR (M) mounting version |
| Speaker:              | 1 x woofer 18" with ferrit magnet<br>Basket material: aluminum<br>Conematerial: cardboard/paper<br>Voice coil woofer in/out wound 4"       |
| Type of speaker:      | Subwoofer  |
| Type of construction: | Vented   |
| Carrying handle:      | 4 pc/pcs   |
| Material:             | Baltic birch plywood, 18 mm  |
| Color:                | Black, matte   |
| Dimensions:           | Width: 56 cm<br>Depth: 76 cm<br>Height: 62.8 cm  |
| Weight:               | 53.25 kg   |
| Cable construction:   | 3 x 1.5 mm <sup>2</sup> H05VV-F  |
| Cable length:         | 2.5 m detachable   |

### Scope of delivery:

1 x bass  
1 x power cord  
1 x user manual