

CELTO iFIX8 G2 2-way Coaxial Speaker white

Big sound in small package, mounting bracket included

Art. No.: 11043568

GTIN:



Features:

- Coaxial transducer for unmatched spatial coherence
- Audiophile grade crossover with right phase topology
- HF compression driver with ketone polymere dome
- Birch multiplex cabinet with tongue and groove assembly
- With mounting bracket
- CELTO ACOUSTIQUE driver
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

Technical specifications:

Power:	Peak: 1000W Program: 500W Rated: 250W AES
Frequency range:	95 - 22000 Hz
Sensitivity:	95 dB (1W/1m)
Max. SPL:	125 dB
Dispersion angle:	80° conical
Impedance:	8 ohms
Attachment system:	Mounting bracket

Connections:	Input: speaker via screw plug-in terminal
Crossover frequency:	Passive 1600 Hz Recommended In subwoofer combination High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 8" with ferrit magnet Basket material: aluminum Voice coil lows 2.5" 1 x annular compression driver 1" Voice coil annular 1.75" Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Type of construction:	Closed Box
Use of brands:	CELTO ACOUSTIQUE driver
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	White, textured coating, painted
Dimensions:	Width: 25 cm Depth: 25 cm Height: 24.3 cm
Weight:	9.60 kg

Scope of delivery:

1 x top
1 x mounting bracket
1 x nut
6 x washer
1 x safety eyelet
2 x screw
2 x knurled screw