

CELTO iFIX8 2-Way Coaxial Speaker white

Big sound in small package, mounting bracket included

Art. No.: 11043611

GTIN:



The article is no longer in our assortment.

Features:

- Real 150 W RMS with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- Audiophile grade crossover with right phase topology
- Highly dynamic and smooth reproduction
- High efficiency for incredible SPL to size ratio
- HF compression driver with titan dome
- Birch multiplex cabinet with tongue and groove assembly
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with mounting bracket
- With rigging points
- Any RAL color available on request
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

Technical specifications:

Power:	Program: 300W Rated: 150W RMS
Frequency range:	95 - 18000 Hz
Sensitivity:	94 dB (1W/1m)
Max. SPL:	122 dB
Dispersion angle:	80° x 80°

Impedance:	12 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Mounting bracket
Flying points:	4 x M8 thread
Connections:	Input: speaker via screw terminal
Crossover frequency:	Passive High-pass 2200 Hz, 12db/oct on LF Low-pass 2200 Hz, 18db/oct on HF Recommended In subwoofer combination Bi-amp mode only with external DSP processor High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 8" with ferrit magnet Diaphragmmaterial: treated titanium Voice coil lows 2" 1 x compression tweeter highs 1" Voice coil compression tweeter highs 1.75"
Type of speaker:	On ceiling/on wall speaker; coaxial speaker; on ceiling/on wall speaker
Type of construction:	Closed Box
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	White, textured coating, painted; any RAL color available on request
Dimensions:	Width: 25 cm Depth: 25 cm Height: 24.3 cm
Weight:	8.00 kg

Scope of delivery:

1 x top
1 x nut
2 x washer
1 x safety eyelet
1 x mounting bracket
2 x knurled screw