

CELTO ACOUSTIQUE iFIX10 2-Way Coaxial Speaker black

Big sound in small package, mounting bracket included

Art. No.: 11043615 GTIN: 4026397662603











The article is no longer in our assortment.

Features:

- Real 250 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Any RAL color available on request
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Package contents

- 1 x top, 1 x nut, 2 x washer, 1 x safety eyelet, 1 x mounting bracket, 2 x knurled screw

Technical specifications:

Power:	Program: 500W	
	Rated: 250W RMS	
Frequency range:	90 - 18000 Hz	
Sensitivity:	97 dB (1W/1m)	
Max. SPL:	127 dB	
Dispersion angle:	75° x 75°	
Impedance:	8 ohms	

Logistic

EAN / GTIN: 4026397662603 Weight: 13,80 kg Length: 0.41 m Width: 0.39 m Heigth: 0.42 m

Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Connections:	Input: speaker via screw terminal
Crossover frequency:	Passive
	High-pass 1700 Hz, 12db/oct on LF
	Low-pass 1700 Hz, 18db/oct on HF
	Recommended
	In subwoofer combination
	Bi-amp mode only with external DSP processor
	High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer
Speaker:	1 x woofer 10" with ferrit magnet
	Diaphragmmaterial: Ketone-Polymer
	Voice coil lows 2,5"
	1 x compression tweeter highs 1"
	Voice coil compression tweeter highs 1,75"
Type of speaker:	On ceiling/on wall speaker; coaxial speaker
Type of construction:	Closed Box
Material:	Birch multiplex, 15 mm, CNC made with tongue and grove assembly
Color:	Black, textured coating, painted; any RAL color available on request
Dimensions:	Width: 30 cm
	Depth: 30,5 cm
	Height: 30 cm
Weight:	11,80 kg