

## **CELTO ACOUSTIQUE iFIX13S Vented Subwoofer white**

Impressive 13" woofer, compact design

Art. No.: 11043621 GTIN:



## List price: on demand €

incl. 19% VAT.

## Features:

- Real 600 W RMS with accurate deep tones

- Long excursion 13" LF drivers with ±8.5mm linear Xmax
- Trimmed chassis for 15" performance in 12" size cabinet
- Incredible deep tones from ultra compact cabinet
- High efficiency for incredible SPL to size ratio
- Six M8 flying points for added versatility
- Heavy braced cabinet for vibration free dynamic response
- Birch multiplex cabinet with tongue and groove assembly
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels
- With rigging points
- Any RAL color available on request
- Package contents
- 1 x bass

## **Technical specifications:**

Power:	Program: 1000W Rated: 500W RMS
Frequency range:	42 - 1500 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	130 dB

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Dispersion angle:	Omnidirectional
Impedance:	6 ohms
Flying points:	6 x M8 thread
Connections:	Input: speaker via screw terminal
Crossover frequency:	Active mode only
	Recommended
	High-pass 35 Hz, 24db/oct
	Low-pass 120 Hz, 24db/oct
Speaker:	1 x woofer 13,5" with ferrit magnet
	Basket material: aluminum
	Voice coil lows 3"
Type of speaker:	Subwoofer
Type of construction:	Vented
Material:	Birch multiplex, 18 mm, CNC made with tongue and grove assembly
Color:	White, textured coating, painted; any RAL color available on request
Dimensions:	Width: 54,5 cm
	Depth: 50 cm
	Height: 42,3 cm
Weight:	24,10 kg