

CELTO ACOUSTIQUE CMP10 2-way Coaxial Speaker

Art. No.: 11043630 GTIN:





List price: on demand €

incl. 19% VAT.

Features:

- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Rubberized Polyurea coating
- For application areas such as: Concerts/FoH's; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; installation; mobile use; stage; theater; rental; product presentations and lectures; trade fair construction

Package contents

1 x top

Technical specifications:

Power:	Peak: 1200W
	Program: 600W
	Rated: 300W AES
Frequency range:	78 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	128 dB
Dispersion angle:	80° conical
Impedance:	8 ohms
Flying points:	7 x M8 thread

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Control elements:	Mode switch (1+1- / 2+2-)
Connections:	2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	1500 Hz
Speaker:	1 x woofer 10" with ferrit magnet
	Basket material: aluminum
	Voice coil lows 2,5"
	1 x annular compression driver 1" with neodymium magnet
	Voice coil annular 1,75"
	Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	Coaxial speaker; compact cabinet speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
	Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, rubberized Polyurea coating
Dimensions:	Width: 44 cm
	Depth: 29,8 cm
	Height: 30,6 cm
Weight:	15,00 kg