

## CELTO CMP10 2-way Coaxial Speaker

Art. No.: 11043630

GTIN:



**List price: on demand €**

incl. 19% VAT.

### Features:

- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Rubberized Polyurea coating
- For application areas such as: Concerts/FoH's; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; installation; mobile use; stage; theater; rental; product presentations and lectures; trade fair construction

### Logistic

### Technical specifications:

|                   |                                                 |
|-------------------|-------------------------------------------------|
| Power:            | Peak: 1200W<br>Program: 600W<br>Rated: 300W AES |
| Frequency range:  | 78 - 22000 Hz                                   |
| Sensitivity:      | 97 dB (1W/1m)                                   |
| Max. SPL:         | 128 dB                                          |
| Dispersion angle: | 80° conical                                     |
| Impedance:        | 8 ohms                                          |
| Flying points:    | 7 x M8 thread                                   |
| Control elements: | Mode switch (1+1- / 2+2-)                       |

|                       |                                                                                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connections:          | 2 x 4-pol SpeakON mounting version (F)                                                                                                                                                                                  |
| Crossover frequency:  | 1500 Hz                                                                                                                                                                                                                 |
| Speaker:              | 1 x woofer 10" with ferrit magnet<br>Basket material: aluminum<br>Voice coil lows 2.5"<br>1 x annular compression driver 1" with neodymium magnet<br>Voice coil annular 1.75"<br>Diaphragmmaterial: PEEK (H.T. polymer) |
| Type of speaker:      | Coaxial speaker; compact cabinet speaker                                                                                                                                                                                |
| Type of construction: | Vented                                                                                                                                                                                                                  |
| Use of brands:        | CELTO ACOUSTIQUE driver<br>Built with NEUTRIK connector                                                                                                                                                                 |
| Material:             | Birch multiplex                                                                                                                                                                                                         |
| Color:                | Black, rubberized Polyurea coating                                                                                                                                                                                      |
| Dimensions:           | Width: 44 cm<br>Depth: 29.8 cm<br>Height: 30.6 cm                                                                                                                                                                       |
| Weight:               | 15.00 kg                                                                                                                                                                                                                |

**Scope of delivery:**

1 x top