

CELTO ACOUSTIQUE iFIX17S G2 Vented Subwoofer black

Compact 18" subwoofer with 2000 W power









List price: on demand €

incl. 19% VAT.

Features:

Incredible deep tones from ultra compact cabinet

- High efficiency for incredible SPL to size ratio
- Heavy braced cabinet for vibration free dynamic response
- Birch multiplex cabinet with tongue and groove assembly
- With rigging points
- Available in various colors
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x bass, 1 x screw plug-in terminal

Technical specifications:

Power:	Peak: 4000W	
	Program: 2000W	
	Rated: 1000W AES	
Frequency range:	38 - 1200 Hz	
Sensitivity:	99 dB	
Max. SPL:	135 dB	
Dispersion angle:	Omnidirectional	
Impedance:	8 ohms	
Flying points:	8 x M8 thread	

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Connections:	Input: speaker via screw plug-in terminal	
Crossover frequency:	Active mode only	
	Recommended	
	High-pass 30 Hz, 24db/oct	
	Low-pass 120 Hz, 24db/oct	
Speaker:	1 x woofer 18" with ferrit magnet	
	Basket material: aluminum	
	Voice coil lows 3,5"	
Type of speaker:	Subwoofer	
Type of construction:	Vented	
Material:	Birch multiplex, 18 mm, CNC made with tongue and grove assembly	
Color:	Black, textured coating, painted	
Dimensions:	Width: 59,6 cm	
	Depth: 60,0 cm	
	Height: 48,2 cm	
Weight:	32,00 kg	