

CELTO ACOUSTIQUE HX118S Subwoofer

Exclusive design, ultimate exterior finish

Art. No.: 11043642 GTIN:





The article is no longer in our assortment.

Features:

- I	Real	1200	W	RMS	power	capacity
-----	------	------	---	-----	-------	----------

- Premium 18" Neodymium driver with ±11mm linear Xmax
- Triple-forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- Titanium Finish metal parts
- 15-layer piano lacquer finish
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Any RAL color available on request
- For application areas such as: Theater; concerts/FoH's; clubs/dancing school; restaurants, bars and hotels

Technical specifications:

Power:	Program: 2400W Rated: 1200W RMS		
Frequency range:	26 - 110 Hz		
Sensitivity:	100 dB		
Max. SPL:	134 dB		
Dispersion angle:	Omnidirectional		
Impedance:	8 ohms		
Attachment system:	M20 thread		

Logistic

Connections:	Input: speaker via 2 x 4-pol SpeakON mounting version (F)	
Crossover frequency:	Active mode only	
	Recommended	
	High-pass 30 Hz, 24db/oct	
	Low-pass 80-110 Hz when used with HX12	
Speaker:	1 x woofer 18" with neodymium magnet with dua demodulating rings	
	Basket material: aluminum	
	Voice coil woofer in/out wound 4"	
Use of brands:	CELTO ACOUSTIQUE driver	
	Built with NEUTRIK connector	
Material:	Birch multiplex, 25 mm, CNC made with tongue and grove assembly	
Color:	Orange, high-gloss, 15-layer piano lacquer; any RAL color available on request	
Dimensions:	Width: 58 cm	
	Depth: 73 cm	
	Height: 70 cm	
Weight:	55,00 kg	