

CELTO ACOUSTIQUE CT15V 2-way Fullrange Loudspeaker

Perfectly built speaker

Art. No.: 11043673 GTIN:





List price: on demand €

incl. 19% VAT.

Features:

- Horn 90 degree rotatable for horizontal or vertical use

- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- For application areas such as: Concerts/FoH's; clubs/dancing school; installation; mobile use; stage; theater; sports centres/gyms; multi-purpose hall
- Dual flange
- Package contents
- 1 x top

Technical specifications:

| Power: | Peak: 2000W |
|--------------------|------------------------------|
| | Program: 1000W |
| | Rated: 500W AES |
| Frequency range: | 50 - 22000 Hz |
| Sensitivity: | 98 dB (1W/1m) |
| Max. SPL: | 131 dB |
| Dispersion angle: | 80° x 50° rotatable horn |
| Impedance: | 8 ohms |
| Attachment system: | Dual flange: Ø 35mm (0°/10°) |

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| 11 x M8 thread |
|--|
| 2 x 4-pol SpeakON mounting version (F) |
| Passive 1600 Hz |
| 1 x woofer 15" |
| Basket material: aluminum |
| Voice coil lows 3,5" |
| 1 x annular compression driver 1" |
| Voice coil annular 1,75" |
| Diaphragmmaterial: PEEK (H.T. polymer) |
| Compact cabinet speaker |
| Vented |
| CELTO ACOUSTIQUE driver |
| Built with NEUTRIK connector |
| Birch multiplex |
| Black, textured coating, painted |
| Width: 44,5 cm |
| Depth: 41,4 cm |
| Height: 71,0 cm |
| 26,65 kg |
| |