

CELTO ACOUSTIQUE CT15 G3 2-way Fullrange Loudspeaker

Perfectly built speaker









List price: on demand €

incl. 19% VAT.

Features:

- Horn 90 degree rotatable for horizontal or vertical use

- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- For application areas such as: Concerts/FoH's; clubs/dancing school; installation; mobile use; stage; theater; sports centres/gyms; multi-purpose hall
- Dual flange
- Package contents
- 1 x top

Technical specifications:

| Power: | Peak: 3400W Program: 1600W 800W AES |
|--------------------|---|
| Frequency range: | 48 - 22000 Hz |
| Sensitivity: | 98 dB |
| Max. SPL: | 133 dB |
| Dispersion angle: | 80° x 50° rotatable horn |
| Impedance: | 8 ohms |
| Attachment system: | Dual flange: Ø 35mm (0°/10°) |

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Flying points: | 15 x M8 thread |
|-----------------------|--|
| Control elements: | Mode switch (1+1- / 2+2-) |
| Connections: | 2 x 4-pol SpeakON mounting version (F) |
| Crossover frequency: | Passive 1400 Hz |
| Speaker: | Woofer 15" |
| | Basket material: aluminum |
| | Voice coil lows 3,5" |
| | Annular compression driver 1" |
| | Voice coil annular 1,75" |
| | Diaphragmmaterial: PEEK (H.T. polymer) |
| Type of speaker: | Compact cabinet speaker |
| Type of construction: | Vented |
| Use of brands: | CELTO ACOUSTIQUE driver |
| | Built with NEUTRIK connector |
| Material: | Birch multiplex |
| Color: | Black, textured coating, painted |
| Dimensions: | Width: 44,5 cm |
| | Depth: 41,4 cm |
| | Height: 71,0 cm |
| Weight: | 29,85 kg |
| | |