

CELTO PM15 G2 2-Way Fullrange Loudspeaker

True full-range loudspeaker, for fixed installation via 9 M8 flying points

Art. No.: 11043682

GTIN:



Features:

- Horn 90 degree rotatable for horizontal or vertical use
- Complies with DIN 18032-3 (Ball-proof)

Logistic

Technical specifications:

| | |
|----------------------|---|
| Power: | Program: 1400W Rated: 700W RMS |
| Frequency range: | 38 - 22000 Hz |
| Sensitivity: | 98 dB (1W/1m) |
| Max. SPL: | 133 dB |
| Dispersion angle: | 80° x 50° rotatable horn |
| Impedance: | 8 ohms |
| Standard: | DIN 18032-3 (Ball-proof), |
| Connections: | Input: speaker via 2 x speaker built-in socket (F) |
| Crossover frequency: | Passive 1400 Hz, 12db/oct on LF Passive 1400 Hz, 18db/oct on HF Recommended 35 Hz, 24db/oct in full-range mode 60-140 Hz with subwoofer |
| Speaker: | 1 x woofer 13.5" with ferrit magnet |

Basket material: aluminum
Voice coil lows 3.5"
Diaphragmmaterial: PEEK (H.T. polymer)
1 x annular compression driver 1" with ferrit magnet
Voice coil annular 1.75"

| | |
|-----------------------|---|
| Type of speaker: | Compact cabinet speaker |
| Type of construction: | Transmission line |
| Material: | Birch multiplex |
| Color: | Black, textured coating, painted |
| Dimensions: | Width: 41.0 cm Depth: 45.0 cm Height: 72.0 cm |
| Weight: | 34.00 kg |

Scope of delivery:

1 x top