

## CELTO ACOUSTIQUE SU221 Subwoofer









# List price: on demand €

incl. 19% VAT.

#### Features:

- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Rubberized Polyurea coating Package contents
- 1 x bass

### Logistic

EAN / GTIN: 4026397688191 Weight: 120,00 kg Length: 0.91 m Width: 0.70 m Heigth: 1.36 m Bulky product

#### **Technical specifications:**

Power:	Peak: 14400W Program: 7200W Rated: 3600W AES
Frequency range:	28 - 1500 Hz
Sensitivity:	102 dB
Max. SPL:	143 dB
Dispersion angle:	Omnidirectional
Impedance:	4 ohms
Attachment system:	2x M20 thread
Connections:	3 x 4-pol SpeakON mounting version (F)
Crossover frequency:	Active mode only
Speaker:	2 x woofer 21" with ferrit magnet

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Basket material: aluminum Voice coil woofer in/out wound 4,5"
Type of speaker:	Subwoofer
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Material:	Birch multiplex, CNC made with tongue and grove assembly
Color:	Black, rubberized Polyurea coating
Dimensions:	Width: 122,6 cm Depth: 80,5 cm Height: 58,8 cm
Weight:	107,85 kg