

OMNITRONIC TMC-3 Interface incl. VDJ

MIDI controller and audio interface incl. software Virtual DJ LE

Art. No.: 11045044

GTIN: 4026397418729



Features:

- USB controller with integrated 4-channel sound card for DJs
- Play, mix and scratch digital audio like vinyl records
- 2 decks with selectable source: PC signal or line/phono
- Applicable for analog mixer operation without PC
- External output options for PA applications (XLR/RCA)
- Compatible to any MIDI controlled audio software, all MIDI controllers can be edited and freely assigned
- Optimized for control of the powerful audio and video mixing software Virtual DJ
- Supplied with Virtual DJ 7 Limited Edition, can be upgraded at discount price
- Integrated plug&play audio interface with high-resolution AD/DA converters (16 bits/48 kHz), applicable for Windows XP/Vista/7 and Mac OS X
- Supports all standard codecs, e.g. MP3, WAV, WMA, OGG, M4A, AAC, AVI, MPEG
- 2 line/phono inputs, switchable
- Adjustable DJ microphone input
- Master output and booth output with separate level controls
- Additional recording output
- Headphones output with level control for direct monitoring
- 2-channel mixer section:
- 3-band EQ, gain control and level fader per channel
- Ultra-smooth crossfader with adjustable curve
- Cue function with 3 hot cues
- Stereo LED level display
- Extra large track encoder for quick music library browsing
- Dual player section:
- Touch-sensitive jog dials with mode selector: pitch bend, scratch, fast search
- Dedicated sync function (auto beatmatching)

Logistic

EAN / GTIN: 4026397418729

Weight: 2,70 kg

Length: 0.42 m

Width: 0.32 m

Height: 0.12 m

- Master Tempo (tonal pitch remains constant)
- Beat-accurate seamless loop, can be edited
- Effect units with controls for selection and parameters
- Sample players with LED display, and controls for selection and level
- Powered via USB or included PSU
- Incl. USB cable
- Fully functional home version of the software available online under virtualdj.com
- Minimum system requirements PC: Windows XP(SP2)/Vista/7, Pentium IV , 1.6 GHz processor, 1 GB RAM
- Minimum system requirements Mac: OS X 10.4.11, Core Duo, 1.66 GHz processor, 1 GB RAM
- Sample rate: 48 kHz

Technical specifications:

| | |
|--------------------|--|
| Sample rate: | 48 kHz |
| Connections: | Input: line/phono via 2 x stereo RCA Output: rec. via 1 x stereo RCA Output: master via 1 x stereo RCA Output: master via 2 x 3-pin XLR Output: booth via 1 x stereo RCA |
| USB port: | USB 2.0, type B |
| Converter: | 16 bit |
| Dimensions: | Width: 36 cm Depth: 26 cm Height: 7 cm |
| Weight: | 2.20 kg |
| Type: | USB MIDI controller |
| | 5 V DC, 500 mA via USB port or |
| | 5 V DC, 1000 mA via supplied PSU |
| Inputs: | |
| Line/phono: | 2 x stereo RCA, switchable |
| DJ microphone: | 3-pin XLR and 6.3 mm jack, bal. |
| Outputs: | |
| Master: | 3-pin stereo XLR and stereo RCA |
| Booth: | stereo RCA |
| Rec: | stereo RCA |
| Headphones output: | 3.5 mm and 6.3 mm jack, bal. |
| USB port: | 2.0, type B |
| Converter: | 16 bits |
| Sample rate: | 48 kHz |
| Dimensions: | 360 x 260 x 70 mm |

Scope of delivery: