# INTUSØNIC

### INTUSONIC 8SM300T 2x8" Subwoofer white

2 x 8" low-profile installation subwoofer 2 x 150W AES, 2 x 8 ohms

Art. No.: 12604014

GTIN: 5060502923073







## List price: on demand €

incl. 19% VAT.

#### **Description:**

The INTUCAB 8SM300T is a dual 8" compact installation subwoofer, allowing positioning below objects or on-wall in variable directions via an included mounting rail. The dual driver design in separate chambers provides fast transient response and excellent low-frequency performance. Drivers can be wired for separate left/right amplifier channels or in parallel for a mono amplifier setup (note: a separate crossover is required). The 8SM300T is an affordable yet powerful low-end extension to the frequency response of any installed sound system.

#### Features:

- Low-profile installation subwoofer, only 270mm high
- 2 x 8" high-efficiency LF driver
- Terminal strip connections with individual access to both internal drivers, for separate/parallel wiring
- With Holder for wall mounting
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x user manual, 1 x bass, 1 x mounting material

#### **Technical specifications:**

Power:	Rated: 2x 150W AES Program: 2x 300W
Frequency range:	45 - 4000 Hz

#### Logistic

EAN / GTIN: 5060502923073 Weight: 21,00 kg Length: 0.68 m Width: 0.53 m Heigth: 0.35 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Sensitivity:	100 dB
Impedance:	2 x 8 ohms
Attachment system:	Holder for wall mounting
Connections:	Screw terminal
Type of speaker:	Subwoofer
Type of construction:	Vented
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black
Dimensions:	Width: 61 cm
	Depth: 45 cm
	Height: 27 cm
Weight:	19,10 kg