# INTUSØNIC

### INTUSONIC 6FP80R 6" 2-way Outdoor Speaker white

Weather-proof 6" speaker (IP33) with mount, 8 ohms, 130 W

### Art. No.: 12604024

GTIN: 5060502923493









## List price: on demand €

incl. 19% VAT.

#### **Description:**

The INTUSCAPE 6FP80R is the most compact choice to bring background music to any venue's outdoor areas. Its one-shell design from impact-proof ABS resin with a recessed baffle insert provides superior protection against rain. A PP cone woofer and a silk dome tweeter likewise withstand the rigors of outdoor use. Nonetheless, the vented design and the controlled dispersion deliver a pristine sound quality. An internal line transformer with switchable load, a real crossover - not just a capacitor - and our unique cable gland cover as well as the ball head bracket complement the elegant looks of this speaker.

#### ----

### Features:

- Advanced passive crossover for best sound quality
- Power selector switch with 8 ohms operating position
- With Multi-angle ball head bracket with stainless steel rod
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x user manual, 1 x top, 1 x screw plug-in terminal, 2 x nut, 1 x mounting material, 1 x screwing, 1 x lid

#### **Technical specifications:**

IP classification:	IP33
Power:	Rated: 65W AES
	Program: 130W

#### Logistic

EAN / GTIN: 5060502923493 Weight: 3,66 kg Length: 0.25 m Width: 0.21 m Heigth: 0.37 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Frequency range:	65 - 20000 Hz
Sensitivity:	84 dB (1W/1m)
Max. SPL:	105,1 dB
Dispersion angle:	90° x 80°
Impedance:	8 ohms; public address systems 100V
Attachment system:	Multi-angle ball head bracket with stainless steel rod
Power tapping:	5W; 10W; 20W; 40W RMS via selector switch switchable
Connections:	Screw plug-in terminal
Speaker:	Woofer 6"
	Dome tweeter 1"
	Dome drivermaterial: silk with wave guide
Type of speaker:	On ceiling/on wall speaker
Type of construction:	Vented
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black
Dimensions:	Width: 20 cm
	Depth: 15,6 cm
	Height: 28,5 cm
Weight:	3,36 kg