# OMNITRONIC M-22 USB Dynamic Microphone

Dynamic USB microphone with stand

**Art. No.: 13000419**

GTIN: 4026397522136

## List price: 23.68 €

incl. 19% VAT.

### Description:

Dynamic USB microphone with stand

The OMNITRONIC M-22 USB microphone is ideal for podcasters, musicians, journalists and all those who need audio files for websites or multimedia presentations. Connect the M-22 directly to any computer with a USB input for digital recording and get started right away.

The USB microphone comes with a cardioid pickup pattern for excellent feedback suppression and a wide, balanced frequency response for a natural sound. No driver installation is necessary, just plug & play and the microphone is automatically detected.

A cable with USB connection and a microphone holder are also included.

### Features:

- Plugs in directly to any computer with a USB port for digital recordings
- Cardioid pickup pattern for effective feedback elimination
- Encapsulation against the build-up of static charge
- Broad well-balanced frequency range for natural sound
- Ideal for podcasters, musicians, journalists and anyone requiring recordings for websites or multimedia presentations
- Polar pattern: Cardioid
- Control via plug and play
- The device can be connected via USB to the PC
- Compatible with Win XP, Win Vista, Win 7, Win 10, OS X 10,2 or better
- For application areas such as: Party room

**Package contents**

- 1 x microphone, 1 x holder, 1 x user manual

### Logistic

EAN / GTIN: 4026397522136
Weight: 0,40 kg
Length: 0.26 m
Width: 0.10 m
Heigth: 0.09 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

## Technical specifications:

| | |
|---|---|
| Type: | Studio microphone |
| Cable length: | 2,75 m |
| Capsule type: | Dynamic |
| Polar pattern: | Cardioid |
| Frequency range: | 100 - 12000 Hz |
| Sensitivity: | -53 dB |
| Impedance: | 600 Ohm |
| Control: | Plug and play |
| USB port: | Typ B |
| Switch: | On/off switch; Mute control |
| Material: | Plastic |
| Color: | Black |
| PC connect: | Via USB |
| Weight: | 280 g |
| Operating system: | Win XP, Win Vista, Win 7, Win 10, OS X 10,2 or better |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.