

OMNITRONIC UHF-502 2-Channel Wireless Mic System 863-865 MHz

2-channel UHF PLL microphone system

Art. No.: 13053530

GTIN: 4026397603989



The article is no longer in our assortment.

Features:

- 2-channel multifrequency receiver unit and 2 hand-held microphones with UHF PLL technology
- 80 fixed frequencies selectable per channel
- Pilot tone technology (PLL) and noise squelch for interference-free operation
- Automatic frequency scan (AFS) finds interference-free channels
- Easy and error-free synchronization between receiver and transmitters via infrared signal
- LCDs for RF reception level, AF audio level, frequency and channel
- Parallel operation of up to 4 transmission channels is possible without any interference
- Lock function avoids accidental changing of the transmission channel
- 2 separate channels with volume controls
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output, switchable mic/line
- Jack cable included
- Non-diversity system with two removable antennas (BNC connection)
- Microphones with mute switch and color caps for distinction on stage
- Operation of the receiver unit via supplied power unit
- Operation of the microphones via 2 x 1.5 V batteries (type AA), not included
- Receiver unit with aluminum front panel and dimensions for 483 mm rack installation (1U)
- License-free and approved in the EU
- Polar pattern: Cardioid
- Operating range up to 50m with line-of-sight
- UHF 863 - 865 MHz License-free and approved in Europe
- (19") 48.3 cm rack installation

Package contents

- 1 x microphone, 1 x receiver

Logistic

EAN / GTIN: 4026397603989

Weight: 3,00 kg

Length: 0.51 m

Width: 0.39 m

Height: 0.08 m

Technical specifications:

Type:	Wireless set
Power consumption:	5 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Capsule type:	Dynamic
Polar pattern:	Cardioid
Frequency range:	40 - 18000 Hz
S/N ratio:	>80 dB
Sensitivity:	-95 dB
Range:	Range up to 50m with line-of-sight
Frequency band:	UHF 863 - 865 MHz
Frequency selection:	Switchable frequencies
Material:	Metal
Housing design:	(19") 48.3 cm rack installation
Weight:	2,46 kg
Microphone	
Battery:	4 x Mignon (AA) (not included)
Switch:	On/off switch; mute control
Weight:	0,230 kg
Receiver	
Dimensions:	Width: 48,3 cm Depth: 25,3 cm Height: 4,45 cm
Weight:	1,9 kg
System:	Non-diversity, 2 channels
Color code:	CH A = red, CH B = blue
Receiving frequencies:	80
RF power output:	10 mW
Modulation method:	FM
Frequency stability:	10 ppm
Selectivity:	>80 dB
T.H.D.:	<0.1 %
Audio outputs:	
Mic:	2 x XLR, bal.
Mix:	6.3 mm jack, unbal.
Power supply:	
Receiver:	12 V DC via supplied power unit (100-240 V AC, 50/60 Hz)
Dimensions, weight:	
Microphones:	50 x 240 mm (D x L), 230 g (w/o batteries)