

## RELACART UT-222 Bodypack with HM-800S Headset

Bodypack transmitter with PLL multifrequency transmitter, 823-832 + 863-865 MHz

Art. No.: 13055211

GTIN: 4026397566550



**List price: 153.51 €**

incl. 19% VAT.

### Features:

- Pocket transmitter for receivers UR-222S/D and UR-260D
- Durable aluminum alloy housing, applicable for touring
- Incl. headset microphone HM-800S
- Lavalier microphone optional
- Pilot tone technology (PLL) for interference-free operation
- 2 license-free frequency ranges: 823-832 MHz (Duplex Gap) and 863-865 MHz
- 10 groups with 90 fixed frequencies within 11 MHz switching bandwidth
- Parallel operation of up to 9 systems is possible without any interference
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Mute mode
- Adjustable input gain
- RF output power Hi/Low adjustable
- Lock function for prevents undesired changes to settings
- Long battery life for up to 11 hours continuous operation
- License-free and approved in large parts of the EU (please check on a country-by-country basis)

#### transmitter

- OLED display for easy controlling
- Use a operating range up to 80m

#### Microphone

- Polar pattern: Omnidirectional

### Logistic

EAN / GTIN: 4026397566550

Weight: 0,33 kg

Length: 0.29 m

Width: 0.12 m

Heigh: 0.07 m

## Technical specifications:

---

### Transmitter

---

Type:	Bodypack with microphone
Power supply:	3 V DC
Power connection:	Battery/battery pack
Battery:	2 x Mignon (AA) (not included)
Gain:	0 dB -6 dB -12 dB
Display type:	OLED display
Connections:	Output: Mini XLR (M) 4-pin mounting version
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency selection:	90 Switchable frequencys In 10 groups with up to 10 preset frequencies each
Modulation:	FM
RF power output:	10 mW (LO); 40 mW (HI)
Range:	80 m
Switching bandwidth:	11 MHz
Switch:	On/off/mute switch
Material:	Aluminum
Color:	Black
Dimensions:	Width: 6,6 cm Depth: 2,3 cm Height: 8,4 cm
Weight:	190 g

---

### Microphone

---

Type:	Headset
Power supply:	2-10 V DC
Cable length:	1,2 m
Capsule type:	Condenser Size: Ø 5 mm x 6 mm
Polar pattern:	Omnidirectional
Frequency range:	50 - 20000 Hz
Sensitivity:	-47 dB
Impedance:	1800 Ohm
Connector type:	Mini XLR (F) 4-pin
Material:	Metal
Color:	Skin-colored
Weight:	18 g

---