

**RELACART UT-222 Bodypack with HM-600S Headset**  
Bodypack transmitter with PLL multifrequency transmitter, 823-832 + 863-865 MHz

**Art. No.: 13055231**  
GTIN: 4026397700510



**Features:**

- Durable aluminum alloy housing, applicable for touring
- Pilot frequency squelch technology delete wireless RF interference
- 10 groups with 90 fixed frequencies within 11 MHz switching bandwidth
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Adjustable input gain
- RF output power Hi/Low adjustable
- Lock function for prevents undesired changes to settings
- Up to 9 transmitters can be operated in parallel without interference
- transmitter**
- Operating range up to 80m
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe
- OLED display
- microphone**
- Polar pattern: Omnidirectional
- For further information about this product, please refer to the Data Sheet under "Downloads"

**Logistic**

EAN / GTIN: 4026397700510  
Weight: 0,35 kg  
Length: 0.29 m  
Width: 0.12 m  
Heigh: 0.07 m

**Technical specifications:**

Parallel mode:	Max. 9 transmitter
Weight:	0.21 kg
Type:	Bodypack with microphone
Power supply:	3V DC

Power connection:	Battery/battery pack
Battery:	2 x Mignon (AA) (not included)
Gain:	0 dB -6 dB -12 dB
Range:	Range up to 80m
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Switching bandwidth:	11 MHz
RF power output:	UHF 823 - 832 MHz: 10 mW (LO); 40 mW (HI); UHF 863 - 865 MHz: 5 mW (LO); 10 mW (HI)
Modulation:	FM
Frequency selection:	90 switchable frequencies In 10 groups with up to 10 preset frequencies each
Display type:	OLED display
Control elements:	Transmitter power switch (high-low)
Connections:	Output: Mini XLR (M) 4-pin mounting version
Switch:	On/off/mute switch
Material:	Aluminum
Color:	Black
Dimensions:	Width: 6.6 cm Depth: 2.3 cm Height: 8.4 cm
Weight:	0.174 kg
Type:	Headset microphone
Power supply:	2-10V DC
Cable length:	1.2 m
Capsule type:	Condenser Size: Ø 5 mm x 6 mm
Polar pattern:	Omnidirectional
Frequency range:	50 - 18000 Hz
Sensitivity:	-47 dB
Impedance:	1800 Ohm
Connector type:	Mini XLR (F) 4-pin
Color:	Skin-colored
Weight:	0.028 kg

### Scope of delivery:

- 1 x transmitter
- 1 x microphone
- 1 x windshield
- 1 x user manual
- 1 x declaration of conformity