

## RELACART PM-320R In-Ear Bodypack Receiver 626-668 MHz

In-ear stereo wireless receiver with diversity technology

Art. No.: 13055246

GTIN: 4026397712407





# List price: 296.31 €

incl. 19% VAT.

#### **Description:**

The PM-320 is a wireless in-ear monitoring system delivering outstanding sound for live performances, theater and voice applications. Diversity technology guarantees optimum reception quality without interference or dropouts. The system can be operated in mono and stereo mode. The bodypack receiver is 100 g light and offers perfect wearing comfort.

#### Features:

- Stereo pocket receiver with 317 preset channels and 5 user-defined channels for in-ear monitoring
- Sturdy all-metal housing with soft-touch controls, applicable for touring
- Diversity technology for high reception quality
- Pilot frequency squelch technology delete wireless RF interference
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Stereo or mono/mix mode
- Balance (left, right) adjustable
- Limiter and high frequency boost
- Lock function for prevents undesired changes to settings
- Operating range up to 100m with line-of-sight
- Up to 5 transmitters can be operated in parallel without interference
- OLED display
- Charge status indicator

#### Package contents

- 1 x receiver, 1 x user manual, 1 x declaration of conformity

#### Logistic

EAN / GTIN: 4026397712407 Weight: 0,27 kg Length: 0.29 m Width: 0.12 m Heigth: 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

### Technical specifications:

•	
Туре:	In-ear monitor
Battery:	2 x Mignon (AA) (not included)
Frequency range:	25 - 15000 Hz
S/N ratio:	>100 dB
THD:	<0,9 % at 1 kHz
Range:	Range up to 100m with line-of-sight
Frequency band:	UHF 628 - 668 MHz
Diversity:	Antenna diversity
Switching bandwidth:	32 MHz
Frequency stability:	± 0,005 %
Parallel mode:	Max. 5 transmitter
Modulation:	FM, stereo
Frequency selection:	317 switchable frequencies
	In 20 groups
Display type:	OLED display
Display:	Charge status indicator , frequency , channel
Status LED:	Antenna A/B
Connections:	Output: headphones via 1 x 3.5 mm jack (stereo) mounting version
Material:	Aluminum
Dimensions:	Width: 6,5 cm
	Depth: 2,3 cm
	Height: 9 cm
Weight:	0,11 kg