

OMNITRONIC TM-2000 Pocket transmitter

Universal multifrequency pocket transmitter

Art. No.: 13055514 GTIN: 4026397240351





The article is no longer in our assortment.

Features:

- Transmitts microphone signals to a receiver with the same carrier frequency
- Operation in the low-interference UHF band (792.500-814.000 MHz)
- Up to 8 pocket transmitters with 8 receivers can be operated simultaneously
- Frequency and sensitivity switchable via mini switches
- Can also be used for direct instrument pickup
- 837 carrier frequencies switchable in 50 kHz steps
- LCD display with battery capacity and frequency
- Battery capacity transmission to receiver
- For 2 x 1.5 V mignon batteries (type AA)
- Operation range 200 meters
- Connection via Mini XLR socket
- A lavalier microphone or a headset microphone can be ordered separately
- License-free and approved in Germany

Technical specifications:

Battery:	2 x 1.5 V AA Mignon LR06 alkaline manganese included
Frequency range:	40 - 18000 Hz
Frequency band:	UHF
Dimensions:	Width: 6,4 cm
	Depth: 8,2 cm
	Height: 2,4 cm

Logistic

EAN / GTIN: 4026397240351 Weight: 0,35 kg Length: 0.26 m Width: 0.11 m Heigth: 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Carrier frequency:	UHF 792.500-814.000 MHz
Channel 61:	792.500-797.900 MHz
Channel 62:	798.100-805.900 MHz
Channel 63:	806.100-813.900 MHz
Modulation:	FM
Frequency stability:	±0,005 %
T.H.D.:	<0.9% at 1 kHz
Audio bandwidth:	24 MHz
Maximum deviation:	±48 kHz
RF power output:	10 mW
Coverage:	200 m (with line-of-sight)
Current consumption:	<100 mA @ 3V
Audio input:	Mini XLR
Antenna (L):	75 mm
Weight:	190 g