

## OMNITRONIC UHF-202 Wireless Mic System 863.42+864.99MHz

2-channel UHF PLL microphone system

Art. No.: 13063215 GTIN: 4026397478419











# The article is no longer in our assortment.

#### Features:

- 2-channel receiver unit and 2 hand-held microphones with UHF PLL technology
- Operation in the low-interference UHF band (863-865 MHz) with 2 fixed frequencies
- Parallel operation of up to 4 transmission channels is possible without any interference
- 2 separate channels with volume controls and LEDs for carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Jack cable included
- Microphones with mute switch and color caps for distinction on stage
- Matching pocket transmitters can be ordered separately
- License-free and approved in the EU
- Package contents
- 1 x microphone

### **Technical specifications:**

Туре:	Wireless set	
Power consumption:	10,00 W	
Frequency range:	40 - 18000 Hz	
Dimensions:	Width: 21 cm	
	Depth: 4,5 cm	
	Height: 15,5 cm	
Microphone		

#### Logistic

EAN / GTIN: 4026397478419 Weight: 1,36 kg Length: 0.41 m Width: 0.34 m Heigth: 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Battery:	4 x Mignon (AA) (not included)
System:	Non-diversity, 2 channels
Carrier frequency:	863.420 MHz, 864.990 MHz
Coverage:	50 m (with line-of-sight)
RF power output:	10 mW
Modulation method:	F3F
S/N ratio:	>105 dB
Selectivity:	>80 dB
T.H.D.:	<0.5 % at 1 kHz
Audio outputs:	
Mic:	2 x XLR, bal.
Level/impedance:	400 mV, 2.2 kohms
Line:	6.3 mm jack, unbal.
Level/impedance:	200 mV, 2.2 kohms
Power supply	
Receiver:	100-240 V AC, 50/60 Hz via supplied power unit
Dimensions, weight:	
Receiver:	155 x 210 x 45 mm (L x W x H), 455 g
Microphones:	50 x 265 mm (D x L), 175 g