

OMNITRONIC UHF-302 2-Channel Wireless Mic System 823-832/863-865MHz Art. No.: 13063302

2-channel UHF PLL microphone system

GTIN: 4026397649819

**List price: 213.01 €**

incl. 19% VAT.

Features:

- 2-channel multifrequency receiver unit and 2 hand-held microphones with UHF PLL technology
 - 93 preset channels in 10 channel groups
 - Easy and error-free synchronization between receiver and transmitters via infrared signal
 - LCDs for group, frequency and channel
 - LEDs for carrier and audio signal
 - 2 separate channels with volume controls
 - Balanced XLR output per channel
 - Unbalanced 6.3 mm jack for mixed signal output
 - Jack cable included
 - Removable antennas (BNC connection)
 - Incl. mounting brackets for 483 mm rack installation
 - 2 dynamic microphones with cardioid polar pattern and LCD for battery capacity and frequency
 - Matching pocket transmitter can be ordered separately
 - License-free and approved in large parts of the EU (please check on a country-by-country basis)
 - Use a operating range up to 60m
- Receiver**
- Desktop console housing 1 U; (19") 48.3 cm rack installation (provided)
- Microphone**
- Polar pattern: Cardioid

Logistic

EAN / GTIN: 4026397649819
Weight: 2,90 kg
Length: 0.51 m
Width: 0.38 m
Height: 0.07 m

Technical specifications:

Type: Wireless set

Control elements:	Power switch, level control, encoder
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency selection:	93 Switchable frequencys
Modulation:	FM
Frequency stability:	± 0,0010 %
Range:	60 m
Weight:	2,30 kg
Receiver	
Power supply:	100-240 V AC, 50/60 Hz 14 V DC 350 mA
Power consumption:	4 W
Power connection:	Mains input Coaxial power connector (M) Power supply cord with AC adapter (provided)
Number of channels:	2
Frequency range:	50 - 18,000 Hz
S/N ratio:	>80 dB
THD:	<0,5 % at 1 kHz
Display type:	LCD display
Connections:	Output: 1 x line via 6.3 mm plug (unbal.) Output: 2 x Microphone via 3-pin XLR
Material:	Metal
Housing design:	Desktop console housing 1 U (19") 48.3 cm rack installation (provided)
Microphone	
Type:	Transmitter
Power supply:	3 V DC
Power connection:	Battery/battery pack
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)
Display type:	LCD display
RF power output:	10 mW
Switch:	On/off switch
Material:	Plastic
Dimensions:	Length: 25 cm Diameter: Ø 5,1 cm
Weight:	230 g