

OMNITRONIC UHF-E2 Wireless Mic System 823.6/826.1MHz

License-free 2-channel wireless microphone system

Art. No.: 13063320

GTIN: 4026397700794



The article is no longer in our assortment.

Features:

- 2-channel receiver and 2 hand-held microphones with UHF PLL technology
- Easy handling
- 2 separate channels with volume controls and LEDs for carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Microphones with color indication
- Operating range up to 60m with line-of-sight
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- Up to 12 transmitters can be operated in parallel without interference
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile use; mobile djs / entertainer; small rental

receiver

- Desktop console housing
- (19") 48.3 cm rack installation possible 1 U

microphone

- Polar pattern: Cardioid

Package contents

- 1 x receiver, 2 x antenna, 1 x external mains adapter, 2 x microphone, 1 x jack cable, 3 x mounting bracket, 3 x screw, 4 x foot, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397700794

Weight: 2,21 kg

Length: 0.29 m

Width: 0.42 m

Height: 0.07 m

Technical specifications:

Type: Wireless set

Range: Range up to 60m with line-of-sight

| | |
|----------------------|---|
| Frequency band: | UHF 823 - 832 MHz |
| Carrier frequency: | 823,6; 826,1 |
| Parallel mode: | Max. 12 transmitter |
| Modulation: | FM |
| Frequency selection: | Fixed frequencies |
| Color code: | CH A= red, CH B= orange, |
| Weight: | 1,82 kg |
| Receiver | |
| Power supply: | 100-240 V AC, 50/60 Hz 13,5V DC 150 mA |
| Power consumption: | 6 W |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Number of channels: | 2 |
| Frequency range: | 20 - 20000 Hz |
| S/N ratio: | >96 dB |
| THD: | <0,1 % at 1 kHz |
| Housing color: | Black |
| Control elements: | Power switch, level control |
| Connections: | Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR |
| Material: | Metal |
| Housing design: | Desktop console housing (19") 48.3 cm rack installation possible 1 U |
| Weight: | 1 kg |
| Microphone | |
| Type: | Hand-held transmitter |
| Power supply: | 3V DC |
| Power connection: | Battery/battery pack |
| Capsule type: | Dynamic |
| Polar pattern: | Cardioid |
| Battery: | 2 x Mignon (AA) (not included) |
| Frequency range: | 50 - 20000 Hz |
| RF power output: | 10 mW |
| Housing color: | Black |
| Switch: | Mute control |
| Material: | Plastic |
| Dimensions: | Length: 25 cm Diameter: Ø 5,2 cm |
| Weight: | 0,205 kg |