

OMNITRONIC UHF-E2 Wireless Mic System 527.5/529.7MHz

License-free 2-channel wireless microphone system

Art. No.: 13063322 GTIN: 4026397700848

The article is no longer in our assortment.

Features:

- 2-channel receiver and 2 hand-held microphones with UHF PLL technology
- Easy handling
- 2 separate channels with volume controls and LEDs for carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Microphones with color indication
- Operating range up to 60m with line-of-sight
- UHF 518 548 MHz License-free and approved in large parts of Europe
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Up to 12 transmitters can be operated in parallel without interference

receiver

- Desktop console housing
- (19") 48.3 cm rack installation possible 1 U

microphone

Polar pattern: Cardioid

Package contents

1 x receiver, 2 x antenna, 1 x external mains adapter, 2 x microphone, 1 x jack cable, 3 x mounting bracket, 3 x screw, 4 x foot, 1 x user manual, 1 x declaration of conformity

Technical specifications:

Туре:	Wireless set
Range:	Range up to 60m with line-of-sight

Logistic

EAN / GTIN: 4026397700848

Weight: 2,21 kg Length: 0.29 m Width: 0.42 m Heigth: 0.07 m

Carrier frequency: 527,5; 529,7 Parallel mode: Max. 12 transmitter Modulation: FM Frequency selection: Fixed frequencies Color code: CH A= blue, CH B= grey, Weight: 1,82 kg Receiver Power supply: 100-240 V AC, 50/60 Hz 13,5V DC 150 mA Power consumption: 6 W Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19) 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Type: Hand-held transmitter Power supply: 3V DC	Frequency band:	UHF 518 - 548 MHz
Modulation: FM Frequency selection: Fixed frequencies Color code: CH A= blue, CH B= grey, Weight: 1,82 kg Receiver Power supply: 100-240 V AC, 50/80 Hz 13,5V DC 150 mA Power consumption: 6 W Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Capsule type: Dynamic Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Carrier frequency:	527,5; 529,7
Frequency selection: Fixed frequencies	Parallel mode:	Max. 12 transmitter
Color code: CH A= blue, CH B= grey, Weight: 1,82 kg Receiver 100-240 V AC, 50/60 Hz Power supply: 100-240 V AC, 50/60 Hz 13,5V DC 150 mA 6 W Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: -96 dB THD: <0,1 % at 1 kHz	Modulation:	FM
Weight: 1,82 kg Receiver 100-240 V AC, 50/60 Hz Power supply: 100-240 V AC, 50/60 Hz 13,5V DC 150 mA 4 Power consumption: 6 W Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz	Frequency selection:	Fixed frequencies
Receiver 100-240 V AC, 50/60 Hz Power supply: 100-240 V AC, 50/60 Hz 13,5V DC 150 mA 4 Power consumption: 6 W Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz	Color code:	CH A= blue, CH B= grey,
Power supply: 100-240 V AC, 50/60 Hz 13,5V DC 150 mA Power consumption: 6 W Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19°) 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Weight:	1,82 kg
Power consumption: 6 W Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Metal Housing design: Desktop console housing (19°) 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Receiver	
Power consumption: 6 W Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Housing design: Desktop console housing (19°) 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Power supply:	100-240 V AC, 50/60 Hz
Power connection: Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm		13,5V DC 150 mA
mounting version power supply cord with AC adapter (provided) Number of channels: 2 Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19°) 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Power consumption:	6 W
Frequency range: 20 - 20000 Hz S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19°) 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Power connection:	mounting version power supply cord with AC
S/N ratio: >96 dB THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Number of channels:	2
THD: <0,1 % at 1 kHz Housing color: Black Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Frequency range:	20 - 20000 Hz
Housing color: Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	S/N ratio:	>96 dB
Control elements: Power switch, level control Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Material: Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	THD:	<0,1 % at 1 kHz
Connections: Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Housing color:	Black
Material: Metal Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Control elements:	Power switch, level control
Housing design: Desktop console housing (19") 48.3 cm rack installation possible 1 U Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Connections:	
Weight: 1 kg Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Material:	Metal
Microphone Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Housing design:	
Type: Hand-held transmitter Power supply: 3V DC Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Weight:	1 kg
Power supply: Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Microphone	
Power connection: Battery/battery pack Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Type:	Hand-held transmitter
Capsule type: Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Power supply:	3V DC
Polar pattern: Cardioid Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Power connection:	Battery/battery pack
Battery: 2 x Mignon (AA) (not included) Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Capsule type:	Dynamic
Frequency range: 50 - 20000 Hz RF power output: 10 mW Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Polar pattern:	Cardioid
RF power output: Housing color: Black Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Battery:	2 x Mignon (AA) (not included)
Housing color: Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Frequency range:	50 - 20000 Hz
Switch: Mute control Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	RF power output:	10 mW
Material: Plastic Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Housing color:	Black
Dimensions: Length: 25 cm Diameter: Ø 5,2 cm	Switch:	Mute control
Diameter: Ø 5,2 cm	Material:	Plastic
Weight: 0,205 kg	Dimensions:	_
	Weight:	0,205 kg