OMNITRONIC UHF-E4 Wireless Mic System 518.7/520.9/523.1/525.3MHz

License-free 4-channel wireless microphone system

Art. No.: 13063327

GTIN: 4026397700862

List price: 236.81 €

incl. 19% VAT.

Features:

- 4-channel receiver and 4 hand-held microphones with UHF PLL technology
- Easy handling
- 4 separate channels with volume controls and LEDs for carrier signal and audio signal
- Balanced XLR output per channel
- 6.3 mm jack for mixed signal output
- Microphones with color indication
- Operating range up to 60m with line-of-sight
- UHF 518 - 548 MHz License-free and approved in large parts of Europe
- Up to 12 transmitters can be operated in parallel without interference
- For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile use; mobile djs / entertainer; small rental

Receiver

- Desktop console housing
- (19") 48.3 cm rack installation possible 1 U

Microphone

- Polar pattern: Cardioid

Package contents

- 1 x receiver, 2 x antenna, 1 x external mains adapter, 4 x microphone, 1 x jack cable, 3 x mounting bracket, 4 x foot, 13 x screw, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397700862

Weight: 2,78 kg

Length: 0.53 m

Width: 0.29 m

Heigth: 0.07 m

Technical specifications:

Type:	Wireless set
Range:	Range up to 60m with line-of-sight

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Frequency band:	UHF 518 - 548 MHz
Carrier frequency:	518,7; 520,9; 523,1; 525,3
Parallel mode:	Max. 12 transmitter
Modulation:	FM
Frequency selection:	4 fixed frequencies
Weight:	2,16 kg
Receiver	
Power supply:	100-240 V AC, 50/60 Hz 13,5 V DC 150 mA
Power consumption:	6 W
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Number of channels:	4
Frequency range:	20 - 20000 Hz
S/N ratio:	>96 dB
THD:	<0,1 % at 1 kHz
Housing color:	Black
Control elements:	Power switch, level control
Connections:	Output: line via 1 x 6.3 mm plug (unbal.) Output: Microphone via 4 x 3-pin XLR
Material:	Metal
Color:	Black
Housing design:	Desktop console housing (19") 48.3 cm rack installation possible 1 U
Weight:	1 kg
Microphone	
Type:	Hand-held transmitter
Power supply:	3 V DC
Power connection:	Battery/battery pack
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)
Frequency range:	50 - 20000 Hz
RF power output:	10 mW
Housing color:	Black
Switch:	Mute control
Material:	Plastic
Color:	Black
Dimensions:	Length: 25 cm Diameter: Ø 5,2 cm
Weight:	205 g

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.