

PSSO WISE TWO 2-Channel True Diversity Receiver 518-548MHz

License-free true diversity wireless receiver with 2.4GHz iSync control management

Art. No.: 13063391

GTIN: 4026397683097



The article is no longer in our assortment.

Features:

- Professional multifrequency wireless receiver with true diversity reception for stage use
- High-grade components and intelligent features ensure best performance and high reliability
- Ideal for large multi-channel systems
- 100 preset channels in 10 channel groups
- 2.4 GHz iSync - real-time synchronization and monitoring
- Automatic frequency setup
- Pilot frequency squelch technology delete wireless RF interference
- Multifunctional jogdial for menu settings
- Lock function for prevents undesired changes to settings
- Mic/line selector switch
- 2 detachable BNC antennas allow for use with external antenna divider
- 2 receivers can share a single power adapter
- (19") 48.3 cm rack installation 1 U
- Operating range up to 60m with line-of-sight
- UHF 518 - 548 MHz License-free and approved in large parts of Europe
- Up to 26 transmitters in 3 bands can be operated in parallel without interference
- Multicolor LCD display
- Firmware can be updated
- For application areas such as: Mobile use; stage; theater; rental; sports centres/gyms; concerts/FoH's

Package contents

- 1 x receiver, 1 x external mains adapter, 1 x power cord, 3 x antenna, 2 x BNC cable, 1 x jack cable, 1 x adapter cable, 4 x foot, 2 x holder, 2 x windshield, 1 x user manual, 1 x declaration of conformity, 4 x battery

Logistic

EAN / GTIN: 4026397683097

Weight: 3,72 kg

Length: 0.53 m

Width: 0.32 m

Heigh: 0.13 m

Technical specifications:

| | |
|----------------------|--|
| Type: | Receiver |
| Power supply: | 100-240 V AC, 50/60 Hz 12-15V DC 1500 mA |
| Power consumption: | 8 W |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Number of channels: | 2 |
| Frequency range: | 50 - 20000 Hz |
| S/N ratio: | >96 dB |
| THD: | <0,1 % at 1 kHz |
| Gain: | Microphone -32 dB to +4 dB Output: -32 dB to +4 dB |
| Range: | Range up to 60m with line-of-sight |
| Frequency band: | UHF 518 - 548 MHz |
| Diversity: | True diversity |
| Parallel mode: | Max. 26 transmitter in 3 bands |
| Modulation: | FM |
| Frequency selection: | 100 switchable frequencies In 10 groups Frequencies automatically scannable |
| Display type: | Multicolor LCD display |
| Control elements: | Power switch, groundlift selector, menu, encoder |
| Connections: | Antenna via 2 x BNC (F) 12-15 V Antenna via 1 x SMA (F) mounting version Output: mic/line via 2 x 3-pin XLR Output: mic/line via 2 x 6.3 mm jack socket (mono) mounting version Output: for audio/data link via 2 x BNC (F) |
| Channels: | Microphon chanal: 2 x mono with mic-line switch via XLR or jack |
| Switch: | Low cut switch |
| Material: | Metal |
| Color: | Black |
| PC connect: | , firmware can be updated |
| Housing design: | (19") 48.3 cm rack installation 1 U |
| Dimensions: | Width: 48 cm Depth: 27 cm Height: 4,3 cm |
| Weight: | 2,91 kg |