

**PSSO WISE ONE 1-Channel True Diversity Receiver 638-668MHz**

License-free true diversity wireless receiver with 2.4GHz iSync control management

Art. No.: 13063395

GTIN: 4026397683042



**List price: 296.31 €**

incl. 19% VAT.

**Features:**

- Professional multifrequency wireless receiver with true diversity reception for stage use
- High-grade components and intelligent features ensure best performance and high reliability
- Ideal for large multi-channel systems (parallel operation possible up to 26 systems)
- 100 preset channels in 10 channel groups
- 2.4 GHz iSync - real-time synchronization and monitoring
- Automatic frequency setup
- Pilot frequency squelch technology delete wireless RF interference
- Multifunctional jogdial for menu settings
- Lock function for prevents undesired changes to settings
- XLR and 6.3 mm jack output
- Mic/line selector switch
- Ground lift switch
- 2 detachable BNC antennas allow for use with external antenna divider
- USB port for software updates
- 2 receivers can share a single power adapter
- Delivery includes practical transport bag with jack cable and power adapter
- License-free and approved in the EU (please check on a country-by-country basis)
- Available frequency ranges: 518-548 MHz, 638-668 MHz, 823-832 MHz and 863-865 MHz
- Multicolor LCD display for easy controlling
- Use a operating range up to 60m with line of sight
- Desktop console housing 1 U
- (19") 48.3 cm rack installation (provided)

**Logistic**

EAN / GTIN: 4026397683042  
 Weight: 2,25 kg  
 Length: 0.41 m  
 Width: 0.33 m  
 Height: 0.07 m

**Package contents**

- 1 x Receiver, 1 x External mains adapter, 1 x Adapter, 3 x Antenna, 3 x Mounting bracket, 9 x Screw, 4 x Feet, 1 x Jack cable, 1 x Adapter cable, 1 x Holder, 1 x Windshield, 1 x User manual, 1 x Declaration of conformity, 2 x Battery

## Technical specifications:

Type:	Receiver
Power supply:	100-240 V AC, 50/60 Hz 12-15 V DC 800 mA
Power consumption:	4 W
Power connection:	Mains input via Coaxial power connector (M) power supply cord with AC adapter (provided)
Number of channels:	1
Frequency range:	50 - 20000 Hz
S/N ratio:	>96 dB
THD:	<0,1 % at 1 kHz
Gain:	Microphone -32 dB to +4 dB Output: -32 dB to +4 dB
Display type:	Multicolor LCD display
Control elements:	Power switch, groundlift selector, menu, encoder
Connections:	Antenna via 2 x BNC (F) 12-15 V Antenna via 1 x SMA (F) mounting version Output: mic/line via 1 x 3-pin XLR Output: mic/line via 1 x 6.3 mm jack socket (mono) mounting version
Channels:	Microphon chanal: 1 x mono with Mic-line switch via XLR or jack
Frequency band:	UHF 638 - 668 MHz
Frequency selection:	100 Switchable frequencys In 10 groups Frequencies automatically scannable
Modulation:	FM
Range:	60 m with line of sight
Switch:	Low cut switch
Diversity:	True diversity
Material:	Metal
Color:	Black
Housing design:	Desktop console housing 1 U (19") 48.3 cm rack installation (provided)
Dimensions:	Width: 21 cm Depth: 27 cm Height: 4,3 cm
Weight:	1,80 kg