

PSSO PXS TWO 2-channel True Diversity Receiver 470-510 MHz

License-free true diversity wireless receiver with auto scan, 3-band EQ & TFT color displays

Art. No.: 13063503

GTIN: 4026397743999



List price: 593.81 €

incl. 19% VAT.

Features:

- Professional multifrequency wireless receiver with true diversity reception for stage use
- High-grade components and intelligent features ensure best performance and high reliability
- Ideal for large multi-channel systems
- Up to 28 transmitters can be operated in parallel without interference
- Operating range up to 200m
- Automatic frequency setup
- Spectrum analysis to identify interference frequencies
- Multifunctional jogdial for menu settings
- 2 detachable BNC antennas allow for use with external antenna divider
- Multicolor TFT display
- Charge status indicator
- (19") 48.3 cm rack installation 1 U

Package contents

- 1 x receiver, 2 x antenna, 1 x external mains adapter, 1 x transmitter, 1 x USB cable, 1 x jack cable, 1 x mounting bracket, 6 x screw, 1 x battery pack

Logistic

EAN / GTIN: 4026397743999

Weight: 3,42 kg

Length: 0.54 m

Width: 0.41 m

Heigh: 0.07 m

Technical specifications:

Type:	Receiver
Power supply:	100-240 V AC, 50/60 Hz 12V DC 1500 mA
Power consumption:	6 W
Protection class:	Protection class III

Power connection:	Mains input via coaxial power connector (M) power supply cord with AC adapter (provided)
Number of channels:	1
Frequency range:	30 - 19000 Hz
S/N ratio:	>112 dB
THD:	<0,5 % at 1 kHz
Range:	Range up to 200m
Frequency band:	UHF 470 - 510 MHz
Diversity:	True diversity
Switching bandwidth:	40 MHz
Frequency stability:	± 0,001 %
Parallel mode:	Max. 28 transmitter
Frequency selection:	Frequencies automatically scannable
Housing color:	Black
Display type:	Multicolor TFT display
Display:	Frequency , goup , channel , charge status indicator; RF signal level , AF audio level , antenna A/B , Mute
Control elements:	Power switch, encoder, exit, sync button
Status LED:	Power
Connections:	Input: antenna via 2 x BNC (F) 11,54 V Output: antenna via 2 x BNC (F) Output: microphone via 2 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR (M) mounting version
Equalizer:	3-band tone control
USB port:	2 x type C
Material:	Metal
Mounting dimensions:	27 cm x
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,1 cm Depth: 27 cm Height: 4,5 cm
Weight:	2,80 kg
Jack cable	
Dimensions:	Length: 100 cm