

PSSO PXS Dynamic Wireless Microphone 640-690 MHz

Hand-held microphone with battery pack for PXS receivers

Art. No.: 13063511 GTIN: 4026397744033







List price: 177.31 €

incl. 19% VAT.

Features:

- Dynamic hand-held microphone with UHF pilot tone technology (PLL)
- Rugged metal housing
- Polar pattern: Cardioid
- OLED display
- Operating range up to 200m with line-of-sight
- Up to 28 transmitters can be operated in parallel without interference
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Powered by a battery/battery pack
- Battery operation up to 10h
- Charge status indicator
- Package contents
- 1 x transmitter, 1 x battery pack

Technical specifications:

Туре:	Hand-held transmitter
Power connection:	Battery/battery pack built-in Mains input via USB C (W) mounting version
Capsule type:	Dynamic Size: Ø 2,54 mm
Polar pattern:	Cardioid
Battery pack type:	1 x lithium ion 3,7 V, 1000 mAh, 3,7 Wh

Logistic

EAN / GTIN: 4026397744033 Weight: 0,39 kg Length: 0.30 m Width: 0.09 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Battery pack:	Battery operation up to 10h
	Recharging time 3h
Battery:	1 x Mignon (AA) (not included)
Frequency range:	35 - 19000 Hz
Range:	Range up to 200m with line-of-sight
Frequency band:	UHF 640 - 690 MHz
Switching bandwidth:	50 MHz
Parallel mode:	Max. 28 transmitter
RF power output:	20 mW (LO); 30 mW (HI)
Housing color:	Black
Display type:	OLED display
Display:	Frequency , charge status indicator , Mute , RF signal level
Control elements:	Transmitter power switch (high-low)
Switch:	On/off/mute switch
Material:	Metal
Dimensions:	Length: 25,5 cm
	Diameter: Ø 5,0 cm
Weight:	0,29 kg