

OMNITRONIC UHF-600 Bodypack 520-554 MHz

Bodypack transmitter for UHF-600 receivers

Art. No.: 13063609

GTIN: 4026397738766



List price: 59.38 €

incl. 19% VAT.

Features:

- Bodypack transmitter with PLL multifrequency transmitter
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Gain level adjustable in 4 steps
- Operating range up to 60m with line-of-sight
- Up to 12 transmitters can be operated in parallel without interference
- Ultra-low latency
- Multicolor LCD display
- Charge status indicator

microphone

- Polar pattern: Cardioid

Package contents

- 1 x transmitter, 1 x user manual, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397738766

Weight: 0,08 kg

Length: 0.18 m

Width: 0.13 m

Height: 0.04 m

Technical specifications:

Type:	Bodypack with microphone
Power supply:	3V DC 155 mA
Battery:	2 x Mignon (AA) (not included)
Phantom power:	Or 2,48 V DC
Range:	Range up to 60m with line-of-sight
Frequency band:	UHF 522 - 554 MHz
Switching bandwidth:	34 MHz

Parallel mode:	Max. 12 transmitter
RF power output:	20 mW (LO); 30 mW (HI)
Latency:	< 3 ms
Modulation:	FM
Housing color:	Black
Display type:	Multicolor LCD display
Display:	Frequency , charge status indicator , Mute , RF signal level; AF audio level
Control elements:	Gain-switch (high-mid-low)
Connections:	Input: microphone via 1 x mini XLR (M) 3-pin mounting version
Switch:	On/off switch; mute control
Material:	Plastic
Dimensions:	Width: 6,6 cm Depth: 2,8 cm Height: 8,5 cm
Weight:	0,07 kg
Microphone	
Type:	Lavalier microphone
Power supply:	1,5-10V DC
Cable length:	0,9 m
Capsule type:	Condenser Size: Ø 12 mm x 26,5 mm
Polar pattern:	Cardioid
Frequency range:	80 - 18000 Hz
Sensitivity:	-53 dB
Impedance:	600 Ohm
Color:	Black
Weight:	0,02 kg