

## OMNITRONIC QuickBTR-5.0 XLR Aptx Bluetooth 5.0 Receiver

Portable Bluetooth receiver with XLR output, aptX and stereo link mode

Art. No.: 13072197

GTIN: 4026397679182



**List price: 53.43 €**

incl. 19% VAT.

### Description:

QuickBTR-5.0 is a portable Bluetooth receiver that allows you to stream audio signals wirelessly from your Bluetooth devices to mixers or powered speakers. With QuickBTR-5.0, you can simply add Bluetooth streaming to any live sound setup. The latest Bluetooth 5.0 technology with aptX support ensures fast and stable wireless connections and high-quality audio. The stereo audio stream is output as a mono signal via the XLR plug or as a stereo signal via the 3.5 mm TRS jack. You can also wirelessly link two QuickBTR-5.0 together for stereo speaker setups. Setup is simple: plug QuickBTR-5.0 into the XLR input of a mixer or powered speaker, pair your Bluetooth audio device and start playing! The internal battery keeps the receiver running for over 8 hours. Charging is via any USB power source and the included micro USB cable.

### Logistic

EAN / GTIN: 4026397679182

Weight: 0,17 kg

Length: 0.15 m

Width: 0.09 m

Height: 0.03 m

### Features:

- Add Bluetooth capability to any speaker or mixer
- Eliminates troublesome cable runs
- Stereo link mode: pair two receivers for cable-free stereo playback
- Output level switchable: 0 dBu, -20 dBu
- AUX output via 3.5 mm stereo jack
- Multicolored LED indication for functions and battery level indicator
- Supported codecs: AptX, AAC, SBC, aptX low latency
- Use a operating range up to 10m with line of sight

#### Battery pack

- Battery operation up to 8h

#### Package contents

- 1 x Receiver, 1 x USB cable, 1 x User manual

## Technical specifications:

Type:	Audio transmission
Power supply:	5 V DC 500 mA
Power connection:	Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided)
S/N ratio:	>75 dB
Bluetooth:	Version: 5,0 class 2 Profiles: A2DP
Supported codecs:	AptX, AAC, SBC, aptX low latency
Status LED:	Power, pairing, slave mode, signal, charge level
Connections:	Output: 1 x 3-pin XLR (M) mounting version Output: 1 x 3.5 mm jack (stereo) mounting version
Channels:	Input channel: 1 x stereo
Frequency band:	2.4 GHz
Modulation:	GFSK
Range:	10 m with line of sight
Material:	Plastic
Color:	Black
Dimensions:	Width: 2,6 cm Depth: 2,7 cm Height: 11 cm
Weight:	100 g
Battery pack	
Power connection:	Battery/battery pack built-in
Battery pack type:	1 x lithium ion 3,7 V, 300 mAh, 1,1 Wh
Battery pack:	Battery operation up to 8h