

OMNITRONIC QuickBTR-5.0 XLR Aptx Bluetooth 5.0 Receiver

Portable Bluetooth receiver with XLR output, aptX and stereo link mode

Art. No.: 13072197

GTIN: 4026397679182



Description:

QuickBTR-5.0 is a portable Bluetooth receiver that allows you to stream audio signals wirelessly from your Bluetooth devices to mixers or powered speakers. With QuickBTR-5.0, you can simply add Bluetooth streaming to any live sound setup. The latest Bluetooth 5.0 technology with aptX HD support ensures fast and stable wireless connections and high-quality audio. The stereo audio stream is output as a mono signal via the XLR plug or as a stereo signal via the 3.5 mm TRS jack. You can also wirelessly link two QuickBTR-5.0 together for stereo speaker setups. Setup is simple: plug QuickBTR-5.0 into the XLR input of a mixer or powered speaker, pair your Bluetooth audio device and start playing! The internal battery keeps the receiver running for over 8 hours. Charging is via any USB power source and the included micro USB cable.

Logistic

EAN / GTIN: 4026397679182

Weight: 0,14 kg

Length: 0.15 m

Width: 0.10 m

Height: 0.04 m

Features:

- Add Bluetooth capability to any speaker or mixer
- Eliminates troublesome cable runs
- Stereo link mode: pair two receivers for cable-free stereo playback
- Output level switchable: 0 dBu, -20 dBu
- Supported codecs: AptX, aptX HD, AAC, SBC
- Operating range up to 30m with line-of-sight
- 2.4 GHz license-free worldwide
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; restaurants, bars and hotels; small rental

battery pack

- Cordless, flexible and versatile
- Battery operation up to 8h

Technical specifications:

Type:	Audio transmission
Power supply:	5V DC 500 mA
Power connection:	Battery/battery pack built-in Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided)
S/N ratio:	>75 dB
Bluetooth:	Version: 5.0 class 2 Profiles: A2DP
Bluetooth device name:	Pro Audio BT
Supported codecs:	AptX, aptX HD, AAC, SBC
Range:	Range up to 30m with line-of-sight
Frequency band:	2.4 GHz
Modulation:	GFSK
Status LED:	Power, pairing, slave mode, signal, charge status indicator
Connections:	Output: 1 x 3-pin XLR (M) mounting version Output: 1 x 3.5 mm jack (stereo) mounting version
Channels:	Input channel: 1 x stereo
Material:	Plastic
Color:	Black
Dimensions:	Width: 2.6 cm Depth: 2.7 cm Height: 11 cm
Weight:	0.08 kg
Cable length:	0.6 m
Battery pack type:	1 x lithium ion 3.7 V, 300 mAh, 1.1 Wh
Battery pack:	Battery operation up to 8h

Scope of delivery:

1 x receiver
1 x USB cable
1 x user manual