

OMNITRONIC WMT-2M UHF Transmitter, mono

Wireless mono audio transmission system, 823-832 MHz + 863-865 MHz

Art. No.: 13072227 GTIN: 4026397665338

The article is no longer in our assortment.

Features:

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Compatible with wireless modules and microphones of the MOM and DAD series
- 16 channels selectable
- Supports operation and simultaneous charging
- Robust metal fixing clip
- WM-2M camera tripod optional
- Up to 4 transmitters can be operated in parallel without interference transmitter
- UHF 863 865 MHz License-free and approved in Europe
- UHF 823 832 MHz License-free and approved in large parts of Europe
- Operating range up to 50m
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- Powered by a battery/battery pack
- Package contents
- 1 x transmitter, 1 x microphone, 1 x USB cable, 1 x jack cable, 1 x adapter, 1 x user manual, 1 x declaration of conformity

Technical specifications:

Туре:	Bodypack with microphone
Parallel mode:	Max. 4 transmitter

Logistic

EAN / GTIN: 4026397665338 Weight: 0,23 kg Length: 0.21 m Width: 0.10 m Heigth: 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Control elements:	Level control
Weight:	0,15 kg
Transmitter	
Туре:	Pocket transmitter
Power supply:	Or
	5V DC
	3V DC
Power connection:	Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided)
	Battery/battery pack
Battery:	2 x Mignon (AA) (not included)
S/N ratio:	>90 dB
Range:	Range up to 50m
Frequency band:	UHF 863 - 865 MHz; UHF 823 - 832 MHz
Frequency stability:	± 0,01 %
RF power output:	10 mW
Modulation:	FM
Frequency selection:	Switchable frequencies
Pilot frequency:	32,768 kHz
Connections:	Input: microphone via 1 x mini XLR (M) 3-pin mounting version
	Input: line via 1 x 3.5 mm jack (stereo) mounting version
Switch:	On/off switch
Material:	Plastic
Color:	Black
Dimensions:	Width: 6,7 cm
	Depth: 3,0 cm
	Height: 11,2 cm
Weight:	0,08 kg
Microphone	
Туре:	Lavalier microphone
Power connection:	Via Mini XLR (F) 3-pin
Capsule type:	Condenser