

OMNITRONIC RM-105 Receiver Module WAMS-05

Multifrequency receiving unit for WAMS-05

AUDIO LINK)))



Art. No.: 13106986 GTIN: 4026397282719

The article is no longer in our assortment.

Description:

The multifrequency receiving unit RM-105 serves as a replacement part or as an extension for the PA system W.A.M.S.-05. The receiving unit operates in the UHF range of 863.100 - 864.900 MHz. The frequency range is divided into 16 channels, which can be selected as desired. The hand-held microphone HM-105, the transmitter module ALT-105 and the pocket transmitter TM-105 can be used for a wireless signal transmission to the receiving unit as they are tuned to the same frequencies.

Features:

- Receiver as UHF PLL system, suitable for W.A.M.S.-05 system
- Applicable for operating with a second receiver channel or as a replacement
- Operation in the low-interference UHF-band (863,1-864,9 MHz) with 16 frequencies selectable
- LCD for channel and frequency
- Volume control
- LEDs for carrier and audio signals
- License-free and approved in the EU
- Operating range up to 30m

Technical specifications:

Frequency range:	70 - 16000 Hz
Range:	Range up to 30m
Frequency band:	UHF

Logistic

EAN / GTIN: 4026397282719 Weight: 0,17 kg Length: 0.17 m Width: 0.13 m Heigth: 0.06 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Diversity:	True diversity
Dimensions:	Width: 8,8 cm
	Depth: 3,7 cm
	Height: 13,4 cm
Weight:	0,11 kg
System:	PLL multifrequency receiver
Carrier frequency:	UHF 863.100-864.900 MHz
Power supply:	12 V DC, 185 mA
Output voltage:	130 mV max.