


OMNITRONIC STR-500 Bodypack Receiver IEM

Optional pocket receiver for IEM-500

Art. No.: 14013220 GTIN: 4026397404166







incl. 19% VAT.

Features:

- Multifrequency in-ear monitoring receiver set with mini earphones, supplied in a practical transport case
- Operation in the low-interference UHF band
- Pilot frequency squelch technology delete wireless RF interference
- Adjustable headphones output
- Balance (left, right) adjustable
- High frequency boost selectable
- Lock function for prevents undesired changes to settings
- Belt clip
- Charge status indicator
- receiver
- Powered by a battery/battery pack
- UHF 863 865 MHz License-free and approved in Europe Package contents
- 1 x headphones, 1 x receiver, 1 x user manual

Technical specifications:

In-ear monitor
Charge status indicator , RF signal level , frequency
1,2 m
-

Logistic

EAN / GTIN: 4026397404166 Weight: 0,17 kg Length: 0.19 m Width: 0.07 m Heigth: 0.04 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Frequency range:	20 - 20000 Hz
Impedance:	32 Ohm
Connections:	Input: headphones via 1 x 3.5 mm jack (stereo)
Receiver	
Battery:	2 x 1.5 V AA Mignon LR06 alkaline manganese included
Number of channels:	1
Sensitivity:	94 dB
Frequency band:	UHF 863 - 865 MHz
Frequency stability:	± 0,005 %
Modulation:	FM
Frequency selection:	16 switchable frequencies
Connections:	Output: headphones via 1 x 3.5 mm jack (stereo) mounting version
Transducer type:	Dynamic
Switch:	On/off switch
Dimensions:	Width: 16,5 cm
	Depth: 2,3 cm
	Height: 6,4 cm
Weight:	0,14 kg