



The article is no longer in our assortment.

Features:

FUTURELIGHT EYE-15 CW/WW Zoom LED Moving Head Wash

3in1 moving head wash with zoom

- Equipped with 15 x 10 W bicolor LED in cold and warm white
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Compact housing
- 13, 20 or 21 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution
- 5 LED segments independently controllable (3 LEDs x 5 segments)
- Master dimmer
- Motorized zoom with 22-45° beam angle
- Color presets
- Stepless CW/WW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link

Logistic

- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; RDM
- Preprogrammed in LED PC-Control 512

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

Trunk case with castors, PRO version

- For optimal security
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

High-quality safety rope

- For securing loads over people
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x safety bond, 1 x connector

Technical specifications:

FUTURELIGHT EYE-15 CW/WW Zoom LED Moving Head Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	280,00 W
IP classification:	IP20
Lamp type:	LED lamp
Cooling:	Temperature-controlled fan
Control:	DMX; stand-alone; RDM
Preprogrammed in:	LED PC-Control 512
Beam angle (1/2 peak):	22 - 45°
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 34,4 cm Height: 44,5 cm
Weight:	12,10 kg
DMX channels:	13/20/21
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone

Wireless signal transmission:	2.4 GHz (ISM)
Flash-rate:	18 Hz
LED number:	15
LED type:	10 W BCL
Beam angle:	22-45°
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	250 x 344 x 445 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x DMH-90/150/DMB-160/PLB-230

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	8 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	29,5 cm x 27 cm x 41 cm
Middle compartment:	9,5 cm x 54 cm x 46,5 cm
Inside dimensions:	94,5 cm x 56 cm x 46,5 cm
Dimensions:	Width: 102,5 cm Depth: 60,5 cm Height: 72 cm
Weight:	41,90 kg

EUROLITE TPC-10 Coupler, silver

Maximum load BGV C1 (8-fold):	75 kg
Maximum load WLL (4-fold):	150 kg
Tube diameter sector:	48 - 50 mm
Material:	Aluminum
Color:	Silver
Mounting screw:	M10
Dimensions:	Length: 10 cm Width: 3 cm Depth: 9 cm
Weight:	0,16 kg

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

Secured weight (BGV C1):	Max. 15 kg
Design of the core:	6 x 19 FC
Strength classification:	1770
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm ²
Wire surface:	Zinc-plated
Color:	Silver
Temperature range:	-40° C - +100° C
Dimensions:	Length: 100 cm Diameter: Ø 0,40 cm
Weight:	0,10 kg
Length weigth:	0,0554 kg/m