



Features:

ALUTRUSS QUADLOCK 6082-1000 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

EXPAND XPTC1W Truss Cover 100cm white

Flexible truss cover

- Best suited for reproducing light projections
- Extremely stretchable cloth
- Washable (needs to be treated with flame retardant spray afterwards)
- Suitable for all 3- or 4-point systems with 30 cm side length
- Made in Germany
- For application areas such as: Wedding/gala/events; Trade fair and shop fitting

ALUTRUSS QUADLOCK QQGP 50x50cm white RAL 9010

Baseplate for mobile use

Logistic

- Ground plate as truss stand
- For the vertical installation of truss elements
- Easy and quick handling
- Multifunctional use
- Trusspipe: 50 mm
- Made in Europe

ALUTRUSS Wooden Panel 490x490x30mm cable bushing

- Made in Germany

EUROLITE LED TL-3 TCL 3x3W Trusslight

Spot with 3 x 3 W RGB LEDs, mounting hole and IR remote control

- Compact and bright, making it perfect for truss installation
- Equipped with 3 x 3 W 3in1LED in the colors red, green and blue
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Convenient control possible via IR remote control (optional accessory)
- 3, 5 or 8 DMX channels selectable
- Functions: static colors, stepless RGB color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Sound-controlled via built-in microphone
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Ideal for booth construction, stages and any kind of truss
- Ideal for ALUTRUSS 3-POINT SYSTEM DECOLOCK DQ3
- Hanging as well as standing installation possible
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- 3 LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via IR remote control (optional); stand-alone; DMX; sound to light via microphone
- Fixtures available for Light J; LED PC-Control 512; Light Captain
- With a beam angle of 16°

ALUTRUSS QUADLOCK Half Cone Coupler w.Thread M10

- Trusspipe: 50 mm
- Made in Europe

ACCESSORY Hexagonal Screw M10x40mm

- M10 thread

Technical specifications:

Weight: 16.45 kg

ALUTRUSS QUADLOCK 6082-1000 4-way Cross Beam

Setup: Easy installation

Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 100 cm Width: 29 cm Height: 29 cm
Weight:	6.60 kg

EXPAND XPTC1W Truss Cover 100cm white

Color:	White
Dimensions:	Length: 100 cm
Weight:	0.22 kg

ALUTRUS QUADLOCK QQGP 50x50cm white RAL 9010

Trusspipe:	50 mm
Color:	White
Weight:	3.95 kg

ALUTRUS Wooden Panel 490x490x30mm cable bushing

Weight:	4.24 kg
---------	---------

EUROLITE LED TL-3 TCL 3x3W Trusslight

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	12.00 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 8
Cooling:	Passive convection cooling
Control:	IR remote control (optional); stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light'J; LED PC-Control 512; Light Captain
Beam angle:	16°

Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	34°
Housing color:	Black
Dimensions:	Width: 12.1 cm Depth: 10.8 cm Height: 10.4 cm
Weight:	0.90 kg
DMX connection:	3-pin XLR
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ALUTRUSS QUADLOCK Half Cone Coupler w.Thread M10

Trusspipe:	50 mm
Color:	Alu colored
Dimensions:	Length: 6 cm
Weight:	0.11 kg

ACCESSORY Hexagonal Screw M10x40mm

Thread:	M10 thread
Dimensions:	Length: 4 cm
Weight:	0.02 kg

Scope of delivery:

1 x connection set