



The article is no longer in our assortment.

Features:

- Trusspipe: 50 mm
- <p>ALUTRUSS Steel Base Plate round type A
- <p class="featureSatz">Baseplate for mobile use (connectors 6082 included)
- For the vertical installation of truss elements
- Multifunctional use
- High durability
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair and shop fitting; wedding/gala/events
- <p>ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam
- <p class="featureSatz">4-point truss system
- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection set
- <p>ALUTRUSS QUADLOCK End Plate QQGP-Male
- Trusspipe: 50 mm
- Made in Europe

cone

Logistic

- M8 thread
- <p>EUROLITE LCH-36/55M2 Wall mount for monitors
- <p class="featureSatz">Wall mount
- Wall mount for LCD monitors with a diagonal screen size of 915 mm (36") to 1400 mm (55")
- Adjustable tilting angle
- Stable metal version
- VESA standard
- Mounting materials included in the delivery
- <p>EUROLITE TPC-10 Coupler, silver
- <p class="featureSatz">Mounting coupler for 50 mm tube, maximum load WLL 150 kg
- <p>ALUTRUSS QUICK-LOCK Spare Pivot with Pin
- <p class="featureSatz">QUICK-LOCK set
- Accessories for the robust truss system with QUICK-LOCK
- For use with TRI/QUAD system
- Trusspipe: 50 mm
- Made in Europe
- Package contents**
- 2 x splint, 2 x bolt

Technical specifications:

| | |
|------------|-------------|
| Trusspipe: | 50 mm |
| Color: | Alu colored |
| Weight: | 78,56 kg |

ALUTRUSS Steel Base Plate round type A

| | |
|-------------|--------------------------------------|
| Trusspipe: | 50 mm |
| Material: | Steel |
| Color: | Alu colored |
| Dimensions: | Height: 1,60 cm Diameter: Ø 80 cm |
| Weight: | 60 kg |

ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

| | |
|-----------------------------|---|
| Setup: | Easy installation |
| Trusspipe: | 50 mm x 2 mm |
| Welding technique: | TIG-welding |
| Welding material: | AlMg 5 |
| Alloy: | AlMgSi1 T6 |
| Color: | Alu colored |
| Strut diameter x thickness: | 16 x 2mm |
| Dimensions: | Length: 200 cm Width: 29 cm Height: 29 cm |
| Weight: | 10,80 kg |

ALUTRUSS QUADLOCK End Plate QQGP-Male

| | |
|------------|-------------|
| Trusspipe: | 50 mm |
| Color: | Alu colored |
| Weight: | 1,45 kg |
| Cone | |
| Thread: | M8 thread |

EUROLITE LCH-36/55M2 Wall mount for monitors

| | |
|-------------------------------|--|
| Maximum load BGV C1 (8-fold): | 30 kg |
| Maximum load WLL (4-fold): | 60 kg |
| Distance to wall: | 75 mm |
| Dimensions: | Width: 49,8 cm Depth: 7,5 cm Height: 70 cm |
| Weight: | 5,30 kg |
| Interface dimensios: | 498 x 700 mm |
| Distance to wall: | 75 mm |
| Dimensions: | 748 x 498 x 75 mm |

EUROLITE TPC-10 Coupler, silver

| | |
|-------------------------------|---|
| Maximum load BGV C1 (8-fold): | 75 kg |
| Maximum load WLL (4-fold): | 150 kg |
| Tube diameter sector: | 48 - 50 mm |
| Material: | Aluminum |
| Color: | Silver |
| Mounting screw: | M10 |
| Dimensions: | Length: 10 cm Width: 3 cm Depth: 9 cm |
| Weight: | 0,16 kg |

ALUTRUSS QUICK-LOCK Spare Pivot with Pin

| | |
|------------|-------------|
| Trusspipe: | 50 mm |
| Color: | Alu colored |
| Weight: | 0,09 kg |